

# NT-40

6" BR40/PAR38 Open Metal Trim

Type \_\_\_\_\_

Project \_\_\_\_\_

Catalog No. \_\_\_\_\_

Notes \_\_\_\_\_

## FEATURES

**Trim:** Metal trim with 5-1/8" open center.

**Mounting:** Trim includes two coil springs that clip and securely hold the trim into the housing when installed. Replacement coil springs are available (NRA-22).

## COMPATIBLE LAMP / HOUSINGS

### Line Voltage:

100W BR40/PAR38 Max. (NHIC-17/100DWQA)

150W BR40/PAR38 Max. (NH-26Q; NH-27Q; NHR-26Q; NHR-27Q)

## LABELS AND LISTINGS

\* cULus Listed for Damp Location when used with compatible housing




## PRODUCT IMAGES & DIMENSIONS



NT-40



NT-40N



## 6" BR40/PAR38 Open Metal Trim

Catalog No. \_\_\_\_\_

**NT-40** = 6" BR40/PAR38 White Open Metal Trim

**NT-40N** = 6" BR40/PAR38 Open Natural Metal Trim

## Compatible Housings

Catalog No. \_\_\_\_\_

**NH-26Q** = Non-IC New Construction / 150W max

**NHR-26Q** = Non-IC Remodel / 150W max

**NH-27Q** = Shallow Non-IC New Construction / 150W max

**NHR-27Q** = Shallow Non-IC Remodel / 150W max

**NHIC-17/100DWQA** = IC Air-Tight Double Wall New Construction / 100W max

Example: **NT-40** = 6" BR40/PAR38 White Open Metal Trim