



LED InstantFit Lamps

12T8/48-5000 IF 10/1

Philips InstantFit LED Lamp, 4ft (12W / 1600 lm / 5000K)

Philips LED T8 InstantFit Lamps are an ideal energy saving choice for existing linear fluorescent fixtures.

Product data

General Information	
Cap-Base	G13 [Medium Bi-Pin Fluorescent]
Main Application	Industrial
Nominal Lifetime (Nom)	50000 h
Switching Cycle	50000X
B50L70	50000 h
Light Technical	
Color Code	850 [CCT of 5000K]
Initial lumen (Nom)	1650 lm
Luminous Flux (Rated) (Nom)	1650 lm
Correlated Color Temperature (Nom)	5000 K
Color Consistency	<6
Color Rendering Index (Nom)	83
LLMF At End Of Nominal Lifetime (Nom)	70 %
Operating and Electrical	
Input Frequency	50 to 60 Hz
Power (Rated) (Nom)	12 W
Lamp Current (Nom)	60 mA
Starting Time (Nom)	0.5 s

Warm Up Time To 60% Light (Nom)	instant full light s
Power Factor (Nom)	0.9
Voltage (Nom)	120-277 V
Temperature	
T-Ambient (Max)	45 °C
T-Ambient (Min)	-20 °C
T-Storage (Max)	65 °C
T-Storage (Min)	-40 °C
T-Case Maximum (Nom)	40 °C
Controls and Dimming	
Dimmable	No
Mechanical and Housing	
Product Length	1200 mm
Approval and Application	
Energy Saving Product	Yes
Suitable For Accent Lighting	No
Energy Efficiency Label (EEL)	A+

LED InstantFit Lamps


Approbation Marks	CE marking UL certificate RoHS compliance KEMA
	Keur certificate
Energy Consumption kWh/1000 h	14.5 kWh
Product Data	
Order product name	12T8/48-5000 IF 10/1
EAN/UPC - Product	046677453619

Order code	453613
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	10
Material Nr. (12NC)	929001124204
Net Weight (Piece)	0.230 kg

Warnings and Safety

- Perform a visual inspection to ensure lamp holders (or sockets) are not damaged or loose. If the lamp holders (or sockets) are damaged, corroded, charred, blackened or loose, contact a qualified electrician for proper replacement.
- Please refer to the ballast compatibility guide located at www.philips.com/instantfit.



Dimensional drawing



LEDtube 1200mm 12W G13/850

Product	D1	D2	A1	A2	A3
12T8/48-5000 IF 10/1	25.68 mm	28 mm	1198.0 mm	1205.0 mm	1212.0 mm

Photometric data



General Uniform Lighting

LED InstantFit Lamps

