



# LED InstantFit Lamps

## 24T5 LED/HO/48-3500 IF 10/1

Philips LED T5 InstantFit Lamps are an ideal energy saving choice for existing linear fluorescent fixtures.

### Product data

General Information		Voltage (Nom)	
Cap-Base	G5 [ G5]	39-64 V	
Nominal Lifetime (Nom)	50000 h	Temperature	
Switching Cycle	50000X	T-Ambient (Max)	45 °C
B50L70	50000 h	T-Ambient (Min)	-20 °C
		T-Storage (Max)	65 °C
		T-Storage (Min)	-40 °C
Light Technical		Controls and Dimming	
Color Code	835 [ CCT of 3500K]	Dimmable	No
Initial lumen (Nom)	3300 lm	Mechanical and Housing	
Luminous Flux (Rated) (Nom)	3300 lm	Product Length	1100 mm
Correlated Color Temperature (Nom)	3500 K	Approval and Application	
Color Consistency	<5	DesignLights Consortium Qualified Product List	DesignLights Consortium Qualified Product List
Color Rendering Index (Nom)	82	Energy Saving Product	Yes
LLMF At End Of Nominal Lifetime (Nom)	70 %	Approbation Marks	UL certificate RoHS compliance
Operating and Electrical		Product Data	
Input Frequency	40000-80000 Hz	Order product name	24T5 LED/HO/48-3500 IF 10/1
Power (Rated) (Nom)	24 W	EAN/UPC - Product	046677467135
Lamp Current (Max)	600 mA	Order code	467134
Lamp Current (Min)	400 mA	Numerator - Quantity Per Pack	1
Starting Time (Nom)	0.5 s		
Warm Up Time to 60% Light (Nom)	0.5 s		
Power Factor (Nom)	0.9		

# LED InstantFit Lamps


Numerator - Packs per outer box	10
Material Nr. (12NC)	929001283804
Net Weight (Piece)	0.170 kg

Model Number	9290012838
--------------	------------

## Warnings and Safety

- Perform a visual inspection to ensure lamp holders (or sockets) are not damaged or loose. If the lamp holders (or sockets) are damaged, corroded, charred, blackened or loose, contact a qualified electrician for proper replacement.
- Please refer to the ballast compatibility guide located at [www.philips.com/instantfit](http://www.philips.com/instantfit).




## Dimensional drawing



TLED 120V 24-54W 3600lm 3500K G5

Product	D1	D2	A1	A2	A3
24T5 LED/HO/48-3500 IF	15.2 mm	17.8 mm	1147.8 mm	1154.9 mm	1162 mm
10/1					

## Photometric data



## LED InstantFit Lamps

