



# PAR38 LED

# 13.5PAR38/AMB/F40/827/DIM ULW

Philips PAR38 LED Single Optic Lamps with AirFlux Technology improves shopping experience with superior lighting aesthetics and optimal thermal efficiency in a sleek, lightweight design.

#### Product data

General Information		
Cap-Base	E26 [ Single Contact Medium Screw]	
Nominal Lifetime (Nom)	25000 h	
Switching Cycle	50000X	
Technical Type	13.5-90W	
Light Technical		
Color Code	827 [ CCT of 2700K]	
Beam Angle (Nom)	40 °	
Luminous Flux (Nom)	950 lm	
Luminous Flux (Rated) (Nom)	950 lm	
Luminous Intensity (Nom)	1700 cd	
Color Designation	Warm White (WW)	
Rated Beam Angle	40 °	
Correlated Color Temperature (Nom)	2700 K	
Luminous Efficacy (rated) (Nom)	70.37 lm/W	
Color Consistency	<6	
Color Rendering Index (Nom)	80	
LLMF At End Of Nominal Lifetime (Nom)	70 %	
Operating and Electrical		
Input Frequency	50 to 60 Hz	
Power (Rated) (Nom)	13.5 W	

119 mA
90 W
0.5 s
0.5 s
0.9
120 V
65 °C
Yes
Yes
Yes
Energy Star
13.5PAR38/AMB/F40/827/DIM ULW
046677467784
929001292404
1

Datasheet, 2017, May 26 data subject to change

## PAR38 LED

Numerator - Packs per outer box	6
Material Nr. (12NC)	929001292404
Net Weight (Piece)	0.385 kg

# Warnings and Safety


- Suitable for use in damp locations.
- Not for use in totally enclosed luminaires.
- CAUTION: Risk of electric shock do not use where directly exposed to water.
- NOTES: This device complies with Part 18 of the FCC rule. This product may cause interference with other devices. If interference occurs, change the location of the products involved. This RFLD device complies with Canadian ICES-005

## **Dimensional drawing**

Product	D	С
13.5PAR38/AMB/F40/827/DIM ULW	125 mm	135 mm

#### 13.5PAR38/AMB/F40/827/DIM ULW

## Photometric data



Colocial Resonancia 43 Philys Lighting EV. Page 1

