



PAR38 LED

14PAR38/LED/835/F40/GL/DIM FB 1PK 6/1

Philips PAR38 LED Single Optic Lamps with AirFlux Technology improves shopping experience with superior lighting aesthetics and optimal thermal efficiency in a sleek, lightweight design.

Product data

General Information	
Cap-Base	E26 [Single Contact Medium Screw]
Nominal Lifetime (Nom)	25000 h
Switching Cycle	25000X
Technical Type	14-120W

Light Technical	
Color Code	835 [CCT of 3500K]
Beam Angle (Nom)	40 °
Initial lumen (Nom)	1200 lm
Luminous Flux (Rated) (Nom)	1200 lm
Luminous Intensity (Nom)	2500 cd
Color Designation	White (WH)
Rated Beam Angle	40 °
Correlated Color Temperature (Nom)	3500 K
Luminous Efficacy (rated) (Nom)	85.71 lm/W
Color Consistency	<6
Color Rendering Index (Nom)	80
LLMF At End Of Nominal Lifetime (Nom)	70 %

Operating and Electrical	
Input Frequency	50 to 60 Hz
Power (Rated) (Nom)	14 W
Lamp Current (Nom)	120 mA

Wattage Equivalent	120 W
Starting Time (Nom)	0.5 s
Warm Up Time to 60% Light (Nom)	0.5 s
Power Factor (Nom)	0.9
Voltage (Nom)	120 V

Temperature	
T-Case Maximum (Nom)	80 °C

Controls and Dimming	
Dimmable	Yes

Approval and Application	
Suitable For Accent Lighting	Yes


Product Data	
Order product name	14PAR38/AMB/835/F40/GL/DIM/FB/1PK 6/1
EAN/UPC - Product	046677474683
Order code	474684
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	6
Material Nr. (12NC)	929001319004
Net Weight (Piece)	0.385 kg

PAR38 LED

Warnings and Safety

- Suitable for use in damp locations.
- Not for use in totally enclosed luminaires.
- CAUTION: Risk of electric shock - do not use where directly exposed to water.
- NOTES: This device complies with Part 18 of the FCC rule. This product may cause interference with other devices. If interference occurs, change the location of the products involved. This RFLD device complies with Canadian ICES-005


Dimensional drawing



PAR38 120V 14-120W 40D 3500K E26 D


Product	D	C
14PAR38/AMB/835/F40/GL/DIM/FB/1PK 6/1	121 mm	132 mm

Photometric data



General Information 44 Photo Lighting E26 Page 107


LED Classic PAR38 14W E26 835 F40



LED Classic PAR38 14W E26 835 F40


PAR38 LED

Photometric data




LED Classic PAR38 12-14W E26 835 F25-F40

Lifetime



LED Classic PAR38 12-14W E26 835 F25-F40



LED Classic PAR38 12-14W E26 835 F25-F40

