



T5

11T5HE/34-830/IF14/G/DIM 10/1

Philips T5 LED tubes offer an affordable, energy saving retrofit solution. The T5 lamps have been engineered to withstand the test of time with a 50,000-hour lifetime and a limited 5-year warranty to back it up. The lighting performance effectively replaces conventional fluorescent T5 HO or T5 HE lamps. Available in either InstantFit (Type A or Type C) or MainsFit (Type B / Ballast bypass), Philips T5 TLEDs provide a variety of options for any application.

Product data


General Information		Lamp Current (Min)	
Base	G5 [G5]	Starting Time (Nom)	0.5 s
EU RoHS compliant	Yes	Warm Up Time to 60% Light (Nom)	0.5 s
Nominal Lifetime (Nom)	50000 h	UL Type	Type A - works on ballast
Switching Cycle	50000X	Power Factor (Nom)	0.9
Light Technical		Voltage (Nom)	50-80 V
Color Code	830 [CCT of 3000K]	Temperature	
Beam Angle (Nom)	200 °	T-Ambient (Max)	45 °C
Initial lumen (Nom)	1400 lm	T-Ambient (Min)	-20 °C
Color Designation	White (WH)	T-Storage (Max)	65 °C
Correlated Color Temperature (Nom)	3000 K	T-Storage (Min)	-40 °C
Luminous Efficacy (rated) (Nom)	127.00 lm/W	T-Case Maximum (Nom)	70 °C
Color Consistency	<6	Controls and Dimming	
Color Rendering Index (Nom)	82	Dimmable	Yes
LLMF At End Of Nominal Lifetime (Nom)	70 %	Mechanical and Housing	
Operating and Electrical		Bulb Material	Glass
Input Frequency	40000-110000 Hz	Product Length	36 in
Power (Rated) (Nom)	11 W		
Lamp Current (Max)	400 mA		

Approval and Application	
Energy Efficiency Label (EEL)	Not applicable
Energy Saving Product	Yes
Approbation Marks	UL certificate RoHS compliance
Energy Consumption kWh/1000 h	- kWh

Product Data	
Order product name	11T5HE/34-830/IF14/G/DIM 10/1
EAN/UPC - Product	046677476458

Order code	476457
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	10
Material Nr. (12NC)	929001823504
Net Weight (Piece)	0.110 kg
Model Number	9290018235



Dimensional drawing



TLED 900mm HFV11.5-21W 1500lm 3000K ND

Product	D1	D2	A1	A2	A3
11T5HE/34-830/IF14/G/DIM 10/1	15.3 mm	18.4 mm	847.8 mm	854.9 mm	862 mm


Photometric data



LEDtube 11W G5 830 200D DIM IF14


LEDtube 8W G5 830 200D DIM IF10

Photometric data




LEDtube 11W G5 830 200D DIM IF14


Lifetime




LEDtube 8-14W G5 830-850 200D DIM IF10-21



LEDtube 8-14W G5 830-850 200D DIM IF10-21




LEDtube 8-14W G5 830-850 200D DIM IF10-21



LEDtube 8-14W G5 830-850 200D DIM IF10-21

Lifetime



LEDtube 8-14W G5 830-850 200D DIM IF10-21

