



LED InstantFit Lamps

5PL-C/LED/13V/827/IF5/P/2P 20/1

Philips LED T8 InstantFit Lamps are an ideal energy saving choice for existing linear fluorescent fixtures.

Product data

General Information		Voltage (Nom)		120-277 V
Cap-Base	GX23-2 [GX23-2]	Temperature		
Nominal Lifetime (Nom)	50000 h	T-Ambient (Max)	45 °C	
Switching Cycle	50000X	T-Ambient (Min)	-20 °C	
B50L70	50000 h	T-Storage (Max)	65 °C	
Light Technical		T-Storage (Min)	-40 °C	
Color Code	827 [CCT of 2700K]	T-Case Maximum (Nom)	70 °C	
Beam Angle (Nom)	150 °	Controls and Dimming		
Initial lumen (Nom)	520 lm	Dimmable	No	
Luminous Flux (Rated) (Nom)	520 lm	Mechanical and Housing		
Rated Beam Angle	150 °	Product Length	100 mm	
Correlated Color Temperature (Nom)	2700 K	Approval and Application		
Color Consistency	<6	Energy Saving Product	Yes	
Color Rendering Index (Nom)	82	Approbation Marks	UL certificate RoHS compliance	
LLMF At End Of Nominal Lifetime (Nom)	70 %	Product Data		
Operating and Electrical		Order product name	5PL-C/LED/13V/827/IF5/P/2P 20/1	
Input Frequency	50 to 60 Hz	EAN/UPC - Product	046677532352	
Power (Rated) (Nom)	5 W	Order code	532358	
Lamp Current (Max)	50 mA	Numerator - Quantity Per Pack	1	
Lamp Current (Min)	15 mA	Numerator - Packs per outer box	20	
Starting Time (Nom)	0.5 s			
Warm Up Time to 60% Light (Nom)	0.5 s			
Power Factor (Nom)	0.9			


LED InstantFit Lamps

Material Nr. (12NC)	929001884904
Net Weight (Piece)	0.058 kg
Model Number	9290018849

Warnings and Safety

- Perform a visual inspection to ensure lamp holders (or sockets) are not damaged or loose. If the lamp holders (or sockets) are damaged, corroded, charred, blackened or loose, contact a qualified electrician for proper replacement.
- Please refer to the ballast compatibility guide located at www.philips.com/instantfit.


Dimensional drawing




PLED PLC-V 5-13W 550lm 2700K G24d

Product	D	A1	A2	A3
5PL-C/LED/13V/827/IF5/P/2P 20/1	45.7 mm	24.6 mm	101.6 mm	117.6 mm


Photometric data



Technical Information 11 Page Lighting 1/11





LEDtube PLC 13V 5W GX23-2 827 15D ND



LEDtube PLC 13V 5W GX23-2 827 15D ND



LED InstantFit Lamps

Lifetime




LEDtube PLC 13H 5W GX23-2 827 15D ND

LEDtube PLC 13H 5W GX23-2 827 15D ND



LEDtube PLC 13V 5W GX23-2 827 15D ND

LEDtube PLC 13H 5W GX23-2 827 15D ND



LEDtube PLC 13H 5W GX23-2 827 15D ND

LED InstantFit Lamps

