



LED R20

5R20/PER/930/P/E26/DIM 6/1FB T20

Philips R20 LED lamps are the smart alternative to standard incandescent. The traditional lamp design can provide excellent dimming performance with specular energy savings. They provide the beautiful light and dependable performance you expect from LED at an economical price.


Product data

| General Information | |
|---------------------------------------|------------------------------------|
| Base | E26 [Single Contact Medium Screw] |
| EU RoHS compliant | Yes |
| Nominal Lifetime (Nom) | 15000 h |
| Switching Cycle | 50000X |
| Technical Type | 5-45W |
| Light Technical | |
| Color Code | 930 [CCT of 3000K] |
| Beam Angle (Nom) | 110 ° |
| Initial lumen (Nom) | 450 lm |
| Luminous Flux (Rated) (Nom) | 450 lm |
| Color Designation | White (WH) |
| Correlated Color Temperature (Nom) | 3000 K |
| Luminous Efficacy (rated) (Nom) | 90.00 lm/W |
| Color Consistency | <4 |
| Color Rendering Index (Nom) | 90 |
| LLMF At End Of Nominal Lifetime (Nom) | 70 % |
| Operating and Electrical | |
| Input Frequency | 60 Hz |
| Power (Rated) (Nom) | 5 W |
| Lamp Current (Nom) | 65 mA |

| Wattage Equivalent | 45 W |
|---------------------------------|----------------------------------|
| Starting Time (Nom) | 0.5 s |
| Warm Up Time to 60% Light (Nom) | 0.5 s |
| Power Factor (Nom) | 0.7 |
| Voltage (Nom) | 120 V |
| Temperature | |
| T-Case Maximum (Nom) | 70 °C |
| Controls and Dimming | |
| Dimmable | Yes |
| Mechanical and Housing | |
| Bulb Finish | Frosted |
| Product Data | |
| XUCDM.COPY.Product.Title | 5R20/PER/930/P/E26/DIM 6/1FB T20 |
| EAN/UPC - Product | 046677547400 |
| Order code | 547406 |
| Numerator - Quantity Per Pack | 1 |
| Numerator - Packs per outer box | 6 |
| Material Nr. (12NC) | 929002035304 |
| Net Weight (Piece) | 0.050 kg |

LED R20



Dimensional drawing



R20 120V 5-45W 450lm 90D 3000K E26 D

| Product | D | C |
|----------------------------------|-------|--------|
| 5R20/PER/930/P/E26/DIM 6/1FB T20 | 64 mm | 100 mm |


Photometric data



OSRAM Research Ltd. All rights reserved. Page 1/1

LEDbulb 45,65W E26 930 Frosted


LEDbulb 45W E26 R20 930 Frosted



LEDbulb 45W E26 R20 930 Frosted

LED R20

Lifetime



LEDbulb_15K LED

LEDbulb_15K LMP

