



LED BR40

8.8BR40/PER/930/P/E26/DIM 6/1FB T20

Philips BR40 LED lamps are the smart alternative to standard incandescent. The traditional lamp design can provide excellent dimming performance with spectacular energy savings. They provide the beautiful light and dependable performance you expect from LED at an economical price.


Product data

General Information	
Base	E26 [Single Contact Medium Screw]
EU RoHS compliant	Yes
Nominal Lifetime (Nom)	15000 h
Switching Cycle	50000X
Technical Type	8.8-65W
Light Technical	
Color Code	930 [CCT of 3000K]
Beam Angle (Nom)	110 °
Initial lumen (Nom)	800 lm
Luminous Flux (Rated) (Nom)	800 lm
Color Designation	White (WH)
Correlated Color Temperature (Nom)	3000 K
Luminous Efficacy (rated) (Nom)	90.00 lm/W
Color Consistency	<4
Color Rendering Index (Nom)	90
LLMF At End Of Nominal Lifetime (Nom)	70 %
Operating and Electrical	
Input Frequency	60 Hz
Power (Rated) (Nom)	8.8 W
Lamp Current (Nom)	85 mA

Wattage Equivalent	65 W
Starting Time (Nom)	0.5 s
Warm Up Time to 60% Light (Nom)	0.5 s
Power Factor (Nom)	0.7
Voltage (Nom)	120 V
Temperature	
T-Case Maximum (Nom)	70 °C
Controls and Dimming	
Dimmable	Yes
Mechanical and Housing	
Bulb Finish	Frosted
Product Data	
XUCDM.COPY.Product.Title	8.8BR40/PER/930/P/E26/DIM 6/1FB T20
EAN/UPC - Product	046677547424
Order code	547422
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	6
Material Nr. (12NC)	929002035504
Net Weight (Piece)	0.165 kg

LED BR40


Dimensional drawing




BR40 120V 8.8-65W 800lm 3000K E26 D

Product	D	C
8.8BR40/PER/930/P/E26/DIM 6/1FB T20	125 mm	160 mm


Photometric data



LEDbulb 45,65W E26 930 Frosted



LEDbulb 65W E26 BR40 930 Frosted



General Uniform Lightness Page 11

LEDbulb 65W E26 BR40 930 Frosted

LED BR40

Lifetime



LEDbulb_15K LED

LEDbulb_15K LMP

