

## Bulb characteristics

|               |        |
|---------------|--------|
| Dimmable      | Yes    |
| Intended use  | Indoor |
| Lamp shape    | F15    |
| Socket        | E26    |
| Technology    | LED    |
| Type of glass | Clear  |

## Light characteristics

|                             |                    |
|-----------------------------|--------------------|
| Beam angle                  | 300 degree(s)      |
| Color consistency           | 4SDCM              |
| Color rendering index (CRI) | 90                 |
| Color temperature           | 2700-2200 K        |
| Nominal luminous flux       | 500 lumen          |
| Starting time               | <0.5 s             |
| Warm-up time to 60% light   | Instant full light |

## Packaging information

|               |                                         |
|---------------|-----------------------------------------|
| EAN           | 046677547950                            |
| EOC           | 547959                                  |
| Product title | 5.5F15/PER/927-922/CL/G/E26/WGX 1BC T20 |

## Rated values

|                  |               |
|------------------|---------------|
| Rated beam angle | 300 degree(s) |
|------------------|---------------|

## Bulb dimensions

|        |          |
|--------|----------|
| Height | 11.2 cm  |
| Weight | 0.025 kg |
| Width  | 4.7 cm   |

## Durability

|                               |                |
|-------------------------------|----------------|
| Average life (at 2.7 hrs/day) | 15 year(s)     |
| Lumen maintenance factor      | 70%            |
| Nominal lifetime              | 15,000 hour(s) |
| Number of switch cycles       | 20,000         |

## Miscellaneous

|            |     |
|------------|-----|
| EyeComfort | Yes |
|------------|-----|

## Other characteristics

|                 |         |
|-----------------|---------|
| Lamp current    | 60 mA   |
| Mercury content | 0 mg    |
| Efficacy        | 90 lm/W |

## Power consumption

|                    |       |
|--------------------|-------|
| Power factor       | 0.75  |
| Voltage            | 120 V |
| Wattage            | 5.5 W |
| Wattage equivalent | 60 W  |

|                     |                |
|---------------------|----------------|
| Rated lifetime      | 15,000 hour(s) |
| Rated luminous flux | 500 lumen      |
| Rated power         | 5.5 W          |

## Packaging dimensions & weight

|                              |                |
|------------------------------|----------------|
| SAP EAN/UPC - Piece          | 046677547950   |
| EAN/UPC - Case               | 50046677547955 |
| SAP Gross Weight EAN (Piece) | 0.092 kg       |
| Net Weight                   | 0.070 kg       |
| SAP Height (Piece)           | 18.400 cm      |
| SAP Length (Piece)           | 4.800 cm       |
| SAP Width (Piece)            | 14.000 cm      |