



LED B11

Philips LED B11 candles offer energy saving ambiance with the elegant effect of incandescent candles. These designs provides light in an omnidirectional manner, giving lighting designers a long life alternative to standard incandescent sources.


Product data

General Information	
Base	E26 [Single Contact Medium Screw]
EU RoHS compliant	Yes
Nominal Lifetime (Nom)	15000 h
Switching Cycle	20000X
Technical Type	5.5-60W
Light Technical	
Color Code	950 [CCT of 5000K]
Initial lumen (Nom)	500 lm
Color Designation	Daylight
Correlated Color Temperature (Nom)	5000 K
Luminous Efficacy (rated) (Nom)	90.00 lm/W
Color Consistency	<4
Color Rendering Index (Nom)	90
LLMF At End Of Nominal Lifetime (Nom)	70 %
Operating and Electrical	
Input Frequency	60 Hz
Power (Rated) (Nom)	5.5 W
Lamp Current (Nom)	60 mA
Wattage Equivalent	60 W
Starting Time (Nom)	0.5 s

Warm Up Time to 60% Light (Nom)	0.5 s
Power Factor (Nom)	0.7
Voltage (Nom)	120 V
Temperature	
T-Case Maximum (Nom)	60 °C
Controls and Dimming	
Dimmable	Yes
Mechanical and Housing	
Bulb Finish	Clear
Product Data	
XUCDM.COPY.Product.Title	5.5B11/PER/950/CL/G/E26/DIM 1FBT20
EAN/UPC - Product	046677549428
Order code	549428
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	10
Material Nr. (12NC)	929002206404
Net Weight (Piece)	0.016 kg

LED B11


Dimensional drawing




Candle B11 120V5.5-60W500lm5000KE26DCL

Product	D	C
5.5B11/PER/950/CL/G/E26/DIM 1FBT20	35 mm	92 mm


Photometric data



LEDbulb E12 E26 BA11 B11 927 CL-LDD




LEDcandle 60W E26 B11 950 CL




LEDbulb 40,60W E26 950

LED B11

Lifetime



LEDbulb_15K LED



LEDbulb_15K LMP

