



LED BA11

Philips LED BA11 candles offer energy saving ambiance with the elegant effect of incandescent candles. These designs provides light in an omnidirectional manner, giving lighting designers a long life alternative to standard incandescent sources.

Product data

General Information	
Base	E26 [Single Contact Medium Screw]
EU RoHS compliant	Yes
Nominal Lifetime (Nom)	15000 h
Switching Cycle	20000X
Technical Type	6.6-75W

Light Technical	
Color Code	927-922 [CCT of 2700K-2200K]
Initial lumen (Nom)	600 lm
Color Designation	Warm Glow(WG)
Correlated Color Temperature (Nom)	2700-2200 K
Luminous Efficacy (rated) (Nom)	90.00 lm/W
Color Consistency	<4
Color Rendering Index (Nom)	90
LLMF At End Of Nominal Lifetime (Nom)	0.7 %

Operating and Electrical	
Input Frequency	60 Hz
Power (Rated) (Nom)	6.6 W
Lamp Current (Nom)	75 mA
Wattage Equivalent	75 W
Starting Time (Nom)	0.5 s

Warm Up Time to 60% Light (Nom)	0.5 s
Power Factor (Nom)	0.7
Voltage (Nom)	120 V

Temperature	
T-Case Maximum (Nom)	60 °C


Controls and Dimming	
Dimmable	Yes

Mechanical and Housing	
Bulb Finish	Clear

Product Data	
XUCDM.COPY.Product.Title	6.6BA11/PER/927-922/CL/G/E26/WGX T20
EAN/UPC - Product	046677557461
Order code	557462
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	6
Material Nr. (12NC)	929002295604
Net Weight (Piece)	0.017 kg

LED BA11


Dimensional drawing




BA11 6.6-75W 600lm 2700-2200K E26 D CL

Product	D	C
6.6BA11/PER/927-922/CL/G/E26/WGX T20	35 mm	102 mm


Photometric data



LEDbulb BA11 CL



LEDbulb 75W E26 BA11 927 CL




LEDbulb BA11 927 CL

LED BA11

Lifetime



LEDbulb_15K LED



LEDbulb_15K LMP

