



LED BA11

Philips LED BA11 candles offer energy saving ambiance with the elegant effect of incandescent candles. These designs provides light in an omnidirectional manner, giving lighting designers a long life alternative to standard incandescent sources.

Product data

General Information	
Base	E12 [Candelabra Screw]
EU RoHS compliant	Yes
Nominal Lifetime (Nom)	15000 h
Switching Cycle	20000X
Technical Type	6.6-75W

Light Technical	
Color Code	950 [CCT of 5000K]
Initial lumen (Nom)	600 lm
Color Designation	Daylight
Correlated Color Temperature (Nom)	5000 K
Luminous Efficacy (rated) (Nom)	90.00 lm/W
Color Consistency	<4
Color Rendering Index (Nom)	90
LLMF At End Of Nominal Lifetime (Nom)	0.7 %

Operating and Electrical	
Input Frequency	60 Hz
Power (Rated) (Nom)	6.6 W
Lamp Current (Nom)	65 mA
Wattage Equivalent	75 W
Starting Time (Nom)	0.5 s

Warm Up Time to 60% Light (Nom)	0.5 s
Power Factor (Nom)	0.7
Voltage (Nom)	120 V

Temperature	
T-Case Maximum (Nom)	60 °C


Controls and Dimming	
Dimmable	Yes

Mechanical and Housing	
Bulb Finish	Clear

Product Data	
XUCDM.COPY.Product.Title	6.6BA11/PER/950/CL/G/E12/DIM 1FB T20
EAN/UPC - Product	046677557492
Order code	557496
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	6
Material Nr. (12NC)	929002295904
Net Weight (Piece)	0.014 kg

LED BA11



Dimensional drawing



BA11 120V 6.6-75W 600lm 5000K E12 D CL

Product	D	C
6.6BA11/PER/950/CL/G/E12/DIM 1FB T20	35 mm	110 mm


Photometric data



©2020 Philips Lighting B.V. Philips Lighting B.V. Page 1/1

LEDbulb BA11 CL


LEDbulb 75W E12 BA11 950 CL



LEDbulb BA11 950 CL

LED BA11

Lifetime



LEDbulb_15K LED

LEDbulb_15K LMP

