



MasterClass MainsFit (UL Type-B) T8

14.5T8/MAS/48-840/MF21/P/DIM 25/1

Say hello to Philips MasterClass MainsFit (UL Type B) T8 lamps, Designed to be the perfect retrofit solution for traditional fluorescent lamps, they set the standard for performance, longevity (50,000 to 70,000 hours rate life) and efficacy (up to >190 lm/W). This ballast bypass lamp comes with everything needed built into the lamp, including surge suppression, proven energy savings, long life (up to 70k hours), and patented safety features. All lamps in the MasterClass MainsFit family are double-ended to simplify installation.

Product data

General Information	
Cap-Base	G13 [Medium Bi-Pin Fluorescent]
Nominal lifetime	70,000 hour(s)
Switching Cycle	50,000
Lighting Technology	LED
Light Technical	
Color Code	840 [CCT of 4000K]
Beam Angle (Nom)	180 degree(s)
Luminous Flux	2,100 lm
Color Designation	Cool White (CW)
Correlated Color Temperature (Nom)	4000 K
Luminous Efficacy (rated) (Nom)	144.00 lm/W
Color Consistency	6SCDM
Color rendering index (CRI)	80
LLMF At End Of Nominal Lifetime (Nom)	70 %


Operating and Electrical	
Line Frequency	50 to 60 Hz
Input Frequency	50 to 60 Hz
Power Consumption	14.5 W
Lamp Current (Max)	125 mA
Lamp Current (Min)	58 mA
Wattage Equivalent	32 W
Starting Time (Nom)	0.5 s
Warm-up time to 60% light	0.5 s
Power Factor (Fraction)	0.9
Voltage (Nom)	120-277 V
UL Type	UL Type B
Temperature	
T-Case Maximum (Nom)	158 °F

MasterClass MainsFit (UL Type-B) T8

Controls and Dimming	
Dimmable	Only with specific dimmers
Mechanical and Housing	
Bulb Finish	Frosted
Bulb Material	Plastic
Product Length	47-1/4 inch
Bulb Shape	T8
Net Weight (Piece)	0.463 lb
Approval and Application	
Energy Saving Product	Yes
Approval Marks	RoHS compliance UL certificate DLC compliance
EU RoHS compliant	Yes
Ambient temperature range	-4 °F to 113 °F



Application Conditions	
can it be used in closed luminaires	Yes
Product Data	
Order product name	14.5T8/MAS/48-840/MF21/P/DIM 25/1
Full product name	14.5T8/MAS/48-840/MF21/P/DIM 25/1
Order code	579490
Material Nr. (12NC)	929003525604
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	046677579494
Numerator - Packs per outer box	25
EAN/UPC - Case	50046677579499

Dimensional drawing



Product	D1	D2	A1	A2	A3
14.5T8/MAS/48-840/MF21/P/DIM 25/1	1-1/16 inch	1-1/8 inch	47-3/16 inch	47-1/2 inch	47-3/4 inch

Photometric data




General uniform lighting - 14.5T8/MAS/48-840/MF21/P/DIM 25/1

Light Distribution Diagram - 14.5T8/MAS/48-840/MF21/P/DIM 25/1


MasterClass MainsFit (UL Type-B) T8

Photometric data




Spectral Power Distribution Colour - 14.5T8/MAS/48-840/MF21/P/DIM 25/1


Lifetime




FailureRate



Life Expectancy Diagram




Lumen Maintenance Diagram - 14.5T8/MAS/48-840/MF21/P/DIM 25/1



LifetimeVsTc

MasterClass MainsFit (UL Type-B) T8

Lifetime



Lumen Maintenance Diagram - 14.5T8/MAS/48-840/MF21/P/DIM 25/1

