



# LED BR30

## 8.8BR30/CNG/840/FR/P/E26/DIM/120V 6/1CT

Philips BR30 LED lamps are the smart alternative to standard incandescent. The traditional lamp design can provide excellent dimming performance with spectacular energy savings. They provide the beautiful light and dependable performance you expect from LED at an economical price.

### Product data

General Information	
Cap-Base	E26 [Single Contact Medium Screw]
Nominal lifetime	15,000 hour(s)
Switching Cycle	50,000
Lighting Technology	LED
Light Technical	
Color Code	840 [CCT of 4000K]
Beam Angle (Nom)	110 degree(s)
Luminous Flux	650 lm
Color Designation	Cool White (CW)
Correlated Color Temperature (Nom)	4000 K
Luminous Efficacy (rated) (Nom)	73 lm/W
Color Consistency	6DSCM
Color rendering index (CRI)	80
LLMF At End Of Nominal Lifetime (Nom)	70 %
Operating and Electrical	
Line Frequency	60 Hz
Input Frequency	60 Hz
Power Consumption	8.8 W
Lamp Current (Nom)	90 mA
Wattage Equivalent	65 W


Starting Time (Nom)	0.5 s
Warm-up time to 60% light	0.5 s
Power Factor (Fraction)	0.7
Voltage (Nom)	120 V
UL Type	Yes
Temperature	
T-Case Maximum (Nom)	158 °F
Controls and Dimming	
Dimmable	Only with specific dimmers
Mechanical and Housing	
Bulb Finish	Frosted
Bulb Material	Plastic
Bulb Shape	BR30
UL Wet/ damp/ dry location	Damp location
Net Weight (Piece)	0.148 lb
Approval and Application	
EU RoHS compliant	Yes
T20 compliant	No

## LED BR30

Ambient temperature range	-4 °F to 113 °F
Application Conditions	
can it be used in closed luminaires	Yes
Product Data	
Order product name	8.8BR30/CNG/840/FR/P/E26/DIM/120V 6/1CT
Full product name	8.8BR30/CNG/840/FR/P/E26/DIM/120V 6/1CT


Order code	583609
Material Nr. (12NC)	929003620004
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	046677583606
Numerator - Packs per outer box	6
EAN/UPC - Case	50046677583601

## Dimensional drawing




Product	D	C
8.8BR30/CNG/840/FR/P/E26/DIM/120V 6/1CT	3-3/4 inch	5-1/8 inch

## Photometric data




**Light Distribution Diagram - 8.8BR30/CNG/840/FR/P/E26/DIM/120V 6/1CT**



General uniform lighting - 8.8BR30/CNG/840/FR/P/E26/DIM/120V 6/1CT

LED BR30

Photometric data




Spectral Power Distribution Colour - 8.8BR30/CNG/840/FR/P/E26/DIM/120V 6/1CT

Lifetime



Life Expectancy Diagram



Lumen Maintenance Diagram - 8.8BR30/CNG/840/FR/P/E26/DIM/120V 6/1CT

