

Features

- Sealed die-casting profile for outdoor applications
- Replacing 100-175W MH
- Lumen output from 3800-6000lm
- Multitude of voltage configurations: 120-277V and 347V
- Polycarbonate optical lens with UV stabilizers
- Built-in UL class 2 driver, optional for photocell
- Easy installation, contractor-friendly design
- UL/cUL listed and DLC qualified



DLC model



Applications

- Security, pathway and perimeter lighting
- Building entryways and walkways



Specification

Specification/Model	WP45W27V50KDP1	WP50W34V50KDP1	WP70W27V50KDP1	WP75W34V50KDP1
Input Power	45W	50W	70W	75W
Lumens output	3800lm	4000lm	6000lm	6000lm
Efficacy	86 lm/w	81 lm/w	86 lm/w	80 lm/w
CRI	82			
Color Temperature	5000K			
Input Voltage	100-277 VAC	347 VAC	100-277 VAC	347 VAC
Finish Color	Dark Bronze			
Optical Lens	Polycarbonate (UL Recognized) (f1) Suitable for outdoor use with respect to exposure to Ultraviolet Light, Water Exposure and Immersion in accordance with UL 746C			
Mounting	Junction box Mouting or Direct Wall Mounting			
Photocell	120VAC (UL and CSA listed) 3/4in long threaded nipple, 30-45 second time delay, Power Consumption: less than 0.9 watts at 120 VAC			

Ordering Guide




EXAMPLE: WP 45W 27V 50K D C P

Luminaire Type	Power Consumption	Voltage	CCT	Finish	Accessory (Option)	Photocell (Option)
WP Wall Pack	45W 45Watts	27V ¹ 100-277V	27K 2700K	D Dark Bronze (Default)	(Blank) No Cap	(Blank) No Photocell
	50W ² 50Watts	34V 347V	30K 3000K	B Black	C DLC Cap	P1 120V Photocell
	70W 70Watts		40K 4000K	W White		P2 230V/277V Photocell
	75W ² 75Watts		50K 5000K			

NOTES 1. 277V driver operates on 100-277V (50/60 Hz), Specify 120 and 208-277 options only when ordering with photocell.
2. 45W and 70W are limited to 100-277V input only; 50W and 75W are limited to 347V input only.

Dimension

unit: mm/inch



DLC Model with additional cap:

