

Project Name

Location

Prepared By



## SATCO S11903

3W/LED/T5/865/BP

### Notes

[www] 03-09-2021 01:43:20

### General

|                        |                  |
|------------------------|------------------|
| Status                 | Active           |
| Watts                  | 3                |
| Fluorescent Equivalent | 6                |
| Volts                  | 120V-277V        |
| Ballast Type           | Type B           |
| Shape                  | T5               |
| Base                   | Miniature Bi Pin |
| ANSI Base              | G5               |
| Nominal Length         | 9                |
| Finish                 | Frosted          |
| CCT (Kelvin)           | 6500             |
| Temperature            | Daylight         |
| CRI                    | 82               |
| Lumens                 | 270              |
| Beam Spread            | 240              |
| Dimmable               | Non-Dimmable     |
| Hours Rated            | 50000            |
| Lamp Type              | Linear           |
| Technology             | LED              |

### Electrical

|                         |                                          |
|-------------------------|------------------------------------------|
| Ballasting Requirements | No ballast or external driver required   |
| Operating Frequency     | 50/60 Hz                                 |
| Power Factor            | 0.9                                      |
| Operating Temperature   | -25C (-13F) to a maximum of +45C (+113F) |

### Physical

|              |       |
|--------------|-------|
| MOL          | 8.91  |
| MOD          | 0.83  |
| Material     | Glass |
| Weight (lb.) | 0.06  |

### Additional Information

|                    |                                                        |
|--------------------|--------------------------------------------------------|
| Additional Info    | Replaces F6T5/D lamps                                  |
| Shatter-Proof Type | PET Coated                                             |
| Installation Notes | Direct wire 120-277V line voltage; Double ended wiring |
| Warranty           | 5 Year Limited - T5 LED Bulbs - Ballast Bypass         |

### Compliance

|                   |                               |
|-------------------|-------------------------------|
| Safety Listing    | cULus Classified              |
| Location Rating   | Damp                          |
| Energy Star       | No                            |
| California Status | Lawful for sale in California |
| Nevada Status     | Lawful for sale in Nevada     |
| RoHS Compliant    | Yes                           |
| NSF Approved      | Yes - Approved                |

