

Project Name

Location

Prepared By



Notes

[www] 03-22-2021 04:50:55

### General

Status	Active
Watts	18.5
Fluorescent Equivalent	32
Volts	120V-277V
Ballast Type	Type B
Shape	T8
Base	Medium Bi Pin
ANSI Base	G13
Nominal Length	48
Finish	Frosted
CCT (Kelvin)	3500
Temperature	Neutral White
CRI	80
Lumens	2400
Beam Spread	180
Dimmable	Non-Dimmable
Hours Rated	50000
Lamp Type	Linear
Technology	LED

### Electrical

Ballasting Requirements	Ballast Bypass; Direct wire 120-277V line voltage; No ballast or external driver required
Power Factor	0.92
Operating Temperature	-20C (-4F) to a maximum of +45C (+113F)

### Physical

MOL	48
MOD	1
Lens Finish	Frosted
Lens Material	Glass
Weight (lb.)	0.85

### Additional Information

Additional Info	Installation protection - will not light if ballast is not bypassed.
Shatter-Proof Type	PET Coated
Installation Notes	Two Installation Options - 1. Double Ended Wiring or 2. Single Ended Wiring
Warranty	5 Year Limited - T8 LED Bulbs - Ballast Bypass

### Compliance

Safety Listing	cULus Classified
Location Rating	Damp
Energy Star	No
DLC Approved	Yes
DLC ID	PLD6BIXNDD9U

California Status	Lawful for sale in California
Nevada Status	Lawful for sale in Nevada
RoHS Compliant	Yes
FCC Compliant	Yes
NSF Approved	ETL Sanitation listed (conforms to NSF)

