

Project Name

Location

Prepared By



SATCO S16407

24T8/LED/HO-SIGN/60-865/BP

Notes

[www] 03-22-2021 04:50:55

General

Status	Active
Watts	24
Fluorescent Equivalent	75
Volts	120V-277V
Ballast Type	Type B
Shape	T8
Base	Recessed Double Contact HO/VHO
ANSI Base	R17d
Nominal Length	60
Finish	Frosted
CCT (Kelvin)	6500
Temperature	Daylight
CRI	83
Lumens	3100
Beam Spread	360
Dimmable	Non-Dimmable
Hours Rated	50000
Lamp Type	Linear
Technology	LED

Electrical

Ballasting Requirements	Ballast Bypass
Operating Frequency	50/60 Hz
Power Factor	0.9
Operating Temperature	-30C (-22F) to a maximum of +45C (+113F)

Physical

MOL	57.88
MOD	1
Material	Plastic

Additional Information

Installation Notes	No ballast or external driver required; Direct wire 120-277V line voltage; Single ended wiring
Warranty	5 Year Limited - T8 LED Bulbs - Ballast Bypass - Outdoor Sign

Compliance

Safety Listing	cULus Classified
Location Rating	Damp
Energy Star	No
California Status	Lawful for sale in California
Nevada Status	Lawful for sale in Nevada
RoHS Compliant	Yes
NSF Approved	Yes - Approved

