

Notes

uanai 02.15.2021 00:27:5

General	
General	
Status	Active
Watts	13
Fluorescent Equivalent	31
Volts	120V-277V
Ballast Type	Type A/B
Shape	<u>T8</u>
Base	Medium Bi Pin
ANSI Base	G13
Nominal Length	22.5
Finish	Frosted
CCT (Kelvin)	3500
Temperature	Neutral White
CRI	80
Lumens	1800
Beam Spread	160
Dimmable	Non-Dimmable
Hours Rated	50000
Lamp Type	U-Bend
Technology	LED
Electrical	
	Ballast required (Type A) or Ballast
Ballasting Requirements	Bypass (Type B)
Operating Frequency	50/60 Hz
Power Factor	0.9
Operating Temperature	-25C (-13F) to a maximum of +45C (+113F)
Physical	
MOL	22.59
MOD	1
Leg Spacing	1.63
Lens Finish	White
Lens Material	Plastic
Housing Color	White
Additional Information	
Warranty	5 Year Limited - 3 hr per day
Compliance	
	all up Listed for Type Avall
Safety Listing	cULus Listed for Type A; cULus Classified for Type B
Location Rating	Damp
Energy Star	No
DLC Approved	Yes
DLC ID	PLIP7GRMDBS6
California Status	Lawful for sale in California

Nevada Status

RoHS Compliant

FCC Compliant



Yes

Yes





Lawful for sale in Nevada











