

Project Name

Location

Prepared By



Notes

[www] 03-09-2021 01:43:25

General

Status	Active
Watts	13
Fluorescent Equivalent	31
Volts	120V-277V
Ballast Type	Type A/B
Shape	T8
Base	Medium Bi Pin
ANSI Base	G13
Nominal Length	22.5
Finish	Frosted
CCT (Kelvin)	5000
Temperature	Natural Light
CRI	80
Lumens	2000
Beam Spread	160
Dimmable	Non-Dimmable
Hours Rated	50000
Lamp Type	U-Bend
Technology	LED

Electrical

Ballasting Requirements	Ballast required (Type A) or Ballast Bypass (Type B)
Operating Frequency	50/60 Hz
Power Factor	0.9
Operating Temperature	-25C (-13F) to a maximum of +45C (+113F)

Physical

MOL	22.59
MOD	1
Leg Spacing	1.63
Lens Finish	White
Lens Material	Plastic
Housing Color	White

Additional Information

Warranty	5 Year Limited - 3 hr per day
----------	-------------------------------

Compliance

Safety Listing	cULus Listed for Type A; cULus Classified for Type B
Location Rating	Damp
Energy Star	No
DLC Approved	Yes
DLC ID	PLY5P1LK7Z5W; PLL0X0VFL6O
California Status	Lawful for sale in California
Nevada Status	Lawful for sale in Nevada
RoHS Compliant	Yes
FCC Compliant	Yes

NSF Approved

No - Not Approved

