



S29935

12T8/LED/48-835/DR
12 watt T8 LED; Medium bi-pin base; 3500K; 50000 Average rated hours; 1700 lumens



Features

- Direct Replacement - for use on Instant Start and Rapid Start ballasts with no rewiring required*
- Solid State LED lighting
- High efficacy
- DLC Listed
- Compatible with emergency ballasts*
- All glass tube

S29935

*May not be compatible with all rapid start and emergency ballasts.

Ballast required

View:

[Ballast Compatibility Chart](#)

Item Number	UPC	Watts	Fluorescent Equivalent	Lamp Shape	Base	ANSI Base	Lamp Code
S29935	045923299353	12	25W-32W	T8	Medium Bi-Pin	G13	12T8/LED/48-835/DR

Dimmable/Non-Dimmable	Finish	MOL In Inches	MOD In Inches	Initial Lumens	Average Rated Hours	Kelvin Temp	Color
Non-Dimmable	Gloss White	48"	1.00"	1700	50000	3500	Neutral White

CRI	Beam Spread Deg	Operating Temperature	Pack	Package Type	CEC Status	DLC ID:	RoHS Compliant
82	210	-20C (-4F) to a maximum of +45C (+113F)	10	Box	Lawful for sale in California	PLP1EJYV155S DLC Search	Yes

UL or ETL Listed

UL Classification

Warranty



National Toll-Free:
800.43.SATCO
(800.437.2826)
www.satco.com

Distribution Centers:
New York, Florida, Texas,
Washington, California,
Puerto Rico

Corporate Offices:
110 Heartland Blvd.,
Brentwood, NY 11717
800.437.2826 631.243.2022
Fax 631.243.2027

