

SATO	COS	29976
------	-----	-------

15T8/LED/48-835/DR

Notes

www] 03-22-2021 04:50:5

General	
Status	Transitioning
Watts	15
Fluorescent Equivalent	25W-32W
Ballast Type	Type A
Shape	Т8
Base	Medium Bi Pin
ANSI Base	G13
Nominal Length	48
Finish	Gloss
CCT (Kelvin)	3500
Temperature	Neutral White
CRI	82
Lumens	2100
Beam Spread	210
Dimmable	Non-Dimmable
Hours Rated	50000
Lamp Type	Linear
Technology	LED
Electrical	
	Ballast required. Direct Replacement-for use on Instant

Electrical	
Ballasting Requirements	Ballast required. Direct Replacement-for use on Instant Start and Rapid Start ballasts with no rewiring required. May not be compatible with every ballast. Refer to the ballast compatibility chart
Power Factor	0.9
Operating Temperature	-20C (-4F) to a maximum of +45C (+113F)

Physical	
MOL	48
MOD	1

MOD	1
Additional Information	
Warranty	5 Year Limited - T8 LED Bulbs

Compliance		
Safety Listing	cULus	
Location Rating	Damp	
Energy Star	No	
DLC Approved	Yes	
DLC ID	PL5QTGX6T5Q2	
California Status	Lawful for sale in California	
Nevada Status	Lawful for sale in Nevada	
RoHS Compliant	Yes	







