

## S8710

18W/LED/HID/5000K/277-347V E26 18 watt - LED HID Replacement; 5000K; Medium base; 277-347 volts

## Features

- High Lumen Omni-directional LED for Industrial / Commercial applications
- Replaces HID, CFL, and Incandescent
  Ballast by-pass Direct wire only 277 347V
  UL approved for totally enclosed fixtures
  Damp location IP65 rated
  For outdoor & indoor use

- Base up or base down operation (high/low bay and post top)
- Emits no UV light / Contains no mercury (Hg)
- 5 year limited warranty
- cULus listed

## Additional Technical Specifications

- Operating Frequency 50-60HzWorking Voltage AC 250-380V
- Power Factor >0.9

Minimum Compartment Size					
Length	Width	Depth			
8.5 inch	6 inch	6 inch			

Optional accessory: In-line surge protector 80-929



S8710

Item Number	Product Line	UPC	Voltage	Watts	Incandes Equival		Fluores Equiva		HID Equivalent
S8710	Hi-Pro	045923087103	277-347	18	120W		32V	/	70W
Base	ANSI	Lamp Code		Dimm	nable/Non-	Finish	MOL In	MOD I	n Initial

Base	ANSI Base	Lamp Code	Dimmable/Non- Dimmable	Finish	MOL In Inches	MOD In Inches	Initial Lumens
Medium	E26	18W/LED/HID/5000K/277-347V E26	Non-Dimmable	White	6-7/8"	2-3/4"	2200

Average Rated	Kelvin	Color	CRI	Beam Spread	Operating Temperature	Pack	Package Type
Hours	Temp	Coloi	OIXI	Deg	Operating remperature	1 ack	r ackage rype

-20C (-4F) to a maximum of 50000 300 5000 Natural Light 80+ 48 Box +65C (+149F) **RoHS** Compliant Fixture Type UL or ETL Listed **UL** Classification Warranty Yes **Enclosed Rated** Yes cULus - Damp Location Rated 5 Year Limited





Distribution Centers: New York, Florida, Texas, Washington, California, Puerto Rico Corporate Offices: 110 Heartland Blvd., Brentwood, NY 11717 800.437.2826 631.243.2022 Fax 631.243.2027



@2012, Satco Products, Inc. Not responsible for typographical errors. 06/12 S1051