



S8715

80W/LED/HID/5000K/277-347V/EX39
 80 watt - LED HID Replacement; 5000K; Mogul extended base;
 277-347 volts

Features

- High Lumen Omni-directional LED for Industrial / Commercial applications
- Replaces HID, CFL, and Incandescent
- Ballast by-pass - Direct wire only 277 - 347V
- UL approved for totally enclosed fixtures
- Damp location - IP65 rated
- For outdoor & indoor use
- Base up or base down operation (high/low bay and post top)
- Emits no UV light / Contains no mercury (Hg)
- 5 year limited warranty
- Classified under UL 1598C
- Safety chain included

Additional Technical Specifications

- Operating Frequency 50-60Hz
- Working Voltage AC 250-380V
- Power Factor >0.9



S8715

Minimum Compartment Size		
Length	Width	Depth
17.3 inch	9.25 inch	9.25 inch

Optional accessory: In-line surge protector [80-929](#)

Item Number	Product Line	UPC	Voltage	Watts	Incandescent Equivalent	Fluorescent Equivalent	HID Equivalent
S8715	Hi-Pro	045923087158	277-347	80	400W	100W	320W

Base	ANSI Base	Lamp Code	Dimmable/Non-Dimmable	Finish	MOL In Inches	MOD In Inches	Initial Lumens
Mogul Extended	EX39	80W/LED/HID/5000K/277-347V/EX39	Non-Dimmable	White	9-1/4"	5.87"	10640

Average Rated Hours	Kelvin Temp	Color	CRI	Beam Spread Deg	Operating Temperature	Pack	Package Type
50000	5000	Natural Light	80+	300	-20C (-4F) to a maximum of +65C (+149F)	4	Box
DLC ID:		RoHS Compliant	UL or ETL Listed	UL Classification	Warranty		
PLGAQNAN8GJT; PLPQ8D2L6VSD DLC Search		Yes	Yes	cULus - Damp Location Rated	5 Year Limited		



National Toll-Free:
800.43.SATCO
(800.437.2826)
www.satco.com

Distribution Centers:
New York, Florida, Texas,
Washington, California,
Puerto Rico

Corporate Offices:
110 Heartland Blvd.,
Brentwood, NY 11717
800.437.2826 631.243.2022
Fax 631.243.2027

