

S9030

5.5A15/LED/2700K/120V 5.5 watt; A15 LED; Frosted; 2700K; Medium base; 230 Degree beam spread; 120 voltsm spread; 120 volts

Features

- Solid State LED lighting
 A shaped replacement lamp
 Long life
- Dimmable
- Approved for enclosed fixtures

Operating temperature: -20°C (-4°F) to a maximum of +45°C (113°F); Not for use in ovens



S9030

Item Number	UPC	UPC		Watts	Incandescent Equivalent		Power Factor La		Lamp Sh	ape	Base	
S9030 045923090301		0301	120	5.5	40W	40W 0.79		A15		Medium		
ANSI Base	Lamp Code			nable/Non- mmable	Suggested Dimmers	_	Finish		OL In MOD I		Initial Lumens	
E26 5.5	A15/LED/2700K/120V		Dimmable		Compatible dimmers for S	— ⊢r	osted	3-15/16	6" 1-7	/8''	450	
Average Rated Kelvin Color Hours Temp		CRI Beam Spread Deg		ad Ope	Operating Temperature				k Pa	ackage Type		
25000	2700	Warm White	80	230	,	-20C (-4F) to a maximum of +45 (+113F); Not for use in ovens			24/6	5	Box	
ENERGY STAR RoHS Compliant		Fixture Type		UL or ETL Listed	III Classification			1	Warranty			
ENERGY STAR Yes		Enclosed Rated		Yes	cULus - Damp Location Rate				3 Year Limited			



National Toll-Free: 800.43.SATCO (800.437.2826) www.satco.com Distribution Centers: New York, Florida, Texas, Washington, California, Puerto Rico Corporate Offices: 110 Heartland Blvd., Brentwood, NY 11717 800.437.2826 631.243.2022 Fax 631.243.2027



©2012, Satco Products, Inc. Not responsible for typographical errors. 06/12 S1051