

## S9579

6.5ST19/AMB/LED/E26/23K/120V 6.5 watt ST19 LED; Transparent Amber; Medium base; 2300K; 650 lumens; 120 volts

## Features

- · LED with a traditional incandescent look and feel
- Omni-directional light source
- Smooth dimming
  Replaces up to 60 watt lamps
  Long life 15,000 hours
  Damp Location

- UL listed for totally enclosed fixtures

## **Compatible Dimmers**

- Leviton 6674 Universal†
  Cooper TAL06P-C1†
- Lutron Nova TCL

† When used with incandescent dimmers, derate the dimmer's maximum load by 75%. Consult your local electrical code to ensure compliance.

$\begin{array}{c c c c c c c c c c c c c c c c c c c $	Item	Item Number UPC		Voltage	Watts	Incandesce	Incandescent Equivalent		Shape	Base	ANSI Base	
Lamp Code     Dimmable/Non- Dimmable     Finish     MOL In Inches     MOD In Inches     Initial Lumens     Rated Hours     Kervin Temp       6.5ST19/AMB/LED/E26/23K/120V     Dimmable     Transparent Amber     5 3/8"     2.38"     650     15000     2300       CRI     Beam Spread Deg     Operating Temperature of +45°C (113°F)     Pack 24/6     Package Type     RoHS Compliant     UL or ETL Listed     UL Classification       80     360     -20°C (-4°F) to a maximum of +45°C (113°F)     24/6     Box     Yes     Yes     Yes     CULus - Damp Location Rated	S	9579	045923095795	120	6.5	60	60W		T19	Medium	E26	
CRI     Beam Spread Deg     Operating Temperature of +45°C (113°F)     Pack Package Type     RoHS Compliant     UL or ETL Listed     UL Classification       80     360     -20°C (-4°F) to a maximum of +45°C (113°F)     24/6     Box     Yes     Yes     Ves     CULus - Damp Location Rated	Lamp Code					Finish				Rated	Keivin	
CRI     Spread Deg     Operating Temperature     Pack     Type     Compliant     Listed     OL Classification       80     360     -20°C (-4°F) to a maximum of +45°C (113°F)     24/6     Box     Yes     Yes     CULus - Damp Location Rated	6.5ST19/AMB/LED/E26/23K/120V			Dimmable			5 3/8"	2.38"	650	15000	2300	
80     360     of +45°C (113°F)     24/6     Box     Yes     Yes     Yes     Rated	CRI		Operating Temperature		Pack	_ •				UL Classification		
	80	360	. ,		24/6	Box	Yes		Yes		•	
<u>3 Year Limited</u>	Warranty											
					<u>3 Y</u>	ear Limited						



S9579



National Toll-Free: 800.43.SATCO (800.437.2826) www.satco.com Distribution Centers: New York, Florida, Texas, Washington, California, Puerto Rico Corporate Offices: 110 Heartland Blvd., Brentwood, NY 11717 800.437.2826 631.243.2022 Fax 631.243.2027



@2012, Satco Products, Inc. Not responsible for typographical errors. 06/12 S1051