



# S9673

45W/LED/HID/4000K/100-277V EX39  
45 watt - LED HID Replacement; 4000K; Mogul extended base;  
100-277 volts

## Features

- High Lumen Omni-directional LED for Industrial / Commercial applications
- Replaces HID, CFL, and Incandescent
- Ballast by-pass - Direct wire only 100V - 277V
- UL approved for totally enclosed fixtures
- Damp location - IP65 rated
- For outdoor & indoor use
- DLC Qualified
- Base up, base down or horizontal operation
- Emits no UV light / Contains no mercury (Hg)
- 5 year limited warranty
- Classified under UL 1598C

## Additional Technical Specifications

- Power Factor >0.9
- Operating temperature range -20°C to 65°C
- Max Ambient Temp 65°C
- Operating Frequency 50-60Hz
- Working Voltage AC90-305V

| Minimum Compartment Size |           |           |
|--------------------------|-----------|-----------|
| Length                   | Width     | Depth     |
| 17.3 inch                | 9.25 inch | 9.25 inch |

Optional accessory: In-line surge protector [80-929](#)



S9673

| Item Number | Product Line | UPC          | Input Voltage | Watts                 | Incandescent Equivalent | Fluorescent Equivalent | HID Equivalent |                |
|-------------|--------------|--------------|---------------|-----------------------|-------------------------|------------------------|----------------|----------------|
| S9673       | Hi-Pro       | 045923096730 | 100 - 277     | 45                    | 300W                    | 65W                    | 175W           |                |
|             |              |              |               |                       |                         |                        |                |                |
| Base        | ANSI Base    | Lamp Code    |               | Dimmable/Non-Dimmable | Finish                  | MOL In Inches          | MOD In Inches  | Initial Lumens |

| Mogul<br>Extended                                | EX39        | 45W/LED/HID/4000K/100-277V<br>EX39 |     |                    | Non-Dimmable                               | White                       | 10-3/4" | 3.69"                          | 5850         |
|--------------------------------------------------|-------------|------------------------------------|-----|--------------------|--------------------------------------------|-----------------------------|---------|--------------------------------|--------------|
| Average Rated<br>Hours                           | Kelvin Temp | Color                              | CRI | Beam Spread<br>Deg | Operating Temperature                      |                             |         | Pack                           | Package Type |
| 50000                                            | 4000        | Cool White                         | 80+ | 300                | -20C (-4F) to a maximum of<br>+65C (+149F) |                             |         | 12                             | Box          |
| DLC ID:                                          |             | RoHS Compliant                     |     | UL or ETL Listed   |                                            | UL Classification           |         | Warranty                       |              |
| P9VQA6T2; PAPJAPGU<br><a href="#">DLC Search</a> |             | Yes                                |     | Yes                |                                            | cULus - Damp Location Rated |         | <a href="#">5 Year Limited</a> |              |



National Toll-Free:  
800.43.SATCO  
(800.437.2826)  
[www.satco.com](http://www.satco.com)

Distribution Centers:  
New York, Florida, Texas,  
Washington, California,  
Puerto Rico

Corporate Offices:  
110 Heartland Blvd.,  
Brentwood, NY 11717  
800.437.2826 631.243.2022  
Fax 631.243.2027



©2012, Satco Products, Inc. Not responsible for typographical errors. 06/12 S1051