

S9723

15T8/LED/48-850/BP/120-277V 15 watt T8 LED; Medium bi-pin base; 5000K; 50000 average

rated hours; 1800 lumens

Features

- No ballast or external driver required
 Direct wire 120-277V line voltage*
- Single ended wiring; Non-shunted socket
- All glass tube
- -20°C (-4°F) to 45°C (113°F) ambient operating temperature
 Long life: 50,000 hours
 cULus classified Damp location

- 5 year warranty
- DLC listed
- * Install only in non-shunted lampholders

Item Number UPC		Voltage	Watts		Operating Frequency		luorescent Equivalent	Lamp Shape	Kase	
S9723	045923097232		120-277	15	50/60Hz	50/60Hz		25-32	Т8	Medium Bi- Pin
ANSI Base	Lamp Code		Dimmable/Non- Dimmable		Finish	MOL Inch		MOD In Inches	Initial Lumens	Average Rated Hours
G13	15T8/LED/48- 850/BP/120-277V		Non-Dimmable		Gloss White	48	"	1.00"	1800	50000
			D							
Kelvin Temp	Color	CRI	Beam Spread Deg	^d Pack	K CEC S	CEC Status		DLC ID:		RoHS Compliant
5000	Natural Light	82	230	10		Lawful for sale in California		PDQU54Y8; PH37X547 DLC Search		Yes
UL or ETL Listed			UL Classification					Warranty		
Yes			cULus - Damp Location Rated						5 Year Limited	

S9723



National Toll-Free: 800.43.SATCO (800.437.2826) www.satco.com Distribution Centers: New York, Florida, Texas, Washington, California, Puerto Rico Corporate Offices: 110 Heartland Blvd., Brentwood, NY 11717 800.437.2826 631.243.2022 Fax 631.243.2027



@2012, Satco Products, Inc. Not responsible for typographical errors. 06/12 S1051