

S9833

5A19/OMNI/220/LED/40K 5 watt; A19 LED; 4000K; Medium base; 220' beam spread; 120

Features

- Solid State LED lighting
 A shaped replacement lamp
 Long life
 Dimmable

- Approved for enclosed fixtures



S9833

Item Number	Item Number UPC		Voltage Watts Incandesce		escent Equiva	lent Pow	er Factor L	amp Sha	pe Base	
S9833 045923098338		38	120 5		40W			0.86		Medium
ANSI Base	Lamp Code			able/Non- mable		uggested Dimmers	Finish	MOL In Inches	MOD Inche	
E26 5A1	5A19/OMNI/220/LED/40K		Dimmable			ompatible ers for S9833	Frosted	4-3/16"	2-3/8	3" 450
Average Rated Hours Kelvin Temp Colo			CRI Beam Spre			Operatir	perating Temperature			Package Type
25000	25000 4000 Cool V		e 80	220		, ,	(-4F) to a maximum of +45C (+113F)		24	Box
ENERGY STA	RoHS Compliant		Fixture Type			UL or ETL Listed		UL Classification		Warranty
ENERGY STA	R Yes		Enclosed Rated		Υe	es cUL	us - Dam	Damp Location Rated		3 Year Limited