



S9907

17T8/LED/48-850/BP 120-277V
17 watt T8 LED; 5000K; Medium Bi Pin base; 50000 Average
rated hours; 2200 Lumens

Features

- All glass tube
- Direct wire 120-277V line voltage*
- NSF Approved
- No ballast or external driver required
- Built-in shock resistant circuit - (not hot until both ends are installed)

*Existing wiring to both sockets can remain in place

*Will work on both shunted or non-shunted sockets



S9907

Item Number	UPC	Input Voltage	Watts	Lamp Shape	Base	ANSI Base	Lamp Code
S9907	045923099076	120 - 277	17	T8	Medium Bi-Pin	G13	17T8/LED/48-850/BP 120-277V
Dimmable/Non-Dimmable	Finish	MOL In Inches	MOD In Inches	Initial Lumens	Average Rated Hours	Kelvin Temp	Color
Non-Dimmable	White	48"	1.00"	2200	50000	5000	Natural Light
CRI	Beam Spread Deg	Pack	DLC ID:	RoHS Compliant	UL or ETL Listed	UL Classification	Warranty
82	210	10	P6J2ZN31 DLC Search	Yes	Yes	cULus Classified - Damp Location Rated	5 Year Limited



National Toll-Free:
800.43.SATCO
(800.437.2826)
www.satco.com

Distribution Centers:
New York, Florida, Texas,
Washington, California,
Puerto Rico

Corporate Offices:
110 Heartland Blvd.,
Brentwood, NY 11717
800.437.2826 631.243.2022
Fax 631.243.2027



©2012, Satco Products, Inc. Not responsible for typographical errors. 06/12 S1051