



S9915

14T8/LED/48-840/BP 120-277V
 14 watt T8 LED; Medium bi-pin base; 4000K; 50000 average
 rated hours; 1800 lumens

Features

- All glass tube
- Direct wire 120-277V line voltage*
- NSF Approved
- No ballast or external driver required
- Built-in shock resistant circuit - (not hot until both ends are installed)



S9915

*Existing wiring to both sockets can remain in place
 *Will work on both shunted or non-shunted sockets

Item Number	UPC	Voltage	Watts	Fluorescent Equivalent	Lamp Shape	Base	ANSI Base
S9915	045923099151	120-277	14	25W-32W	T8	Medium Bi-Pin	G13

Lamp Code	Dimmable/Non-Dimmable	Finish	MOL In Inches	MOD In Inches	Initial Lumens	Average Rated Hours	Kelvin Temp
14T8/LED/48-840/BP 120-277V	Non-Dimmable	White	48"	1.00"	1800	50000	4000

Color	CRI	Beam Spread Deg	Pack	Package Type	DLC ID:	RoHS Compliant	UL or ETL Listed
Cool White	82	220	10	Box	PTTQD4BR DLC Search	Yes	Yes

UL Classification	Warranty
cULus - Damp Location Rated	5 Year Limited



National Toll-Free:
800.43.SATCO
(800.437.2826)
www.satco.com

Distribution Centers:
New York, Florida, Texas,
Washington, California,
Puerto Rico

Corporate Offices:
110 Heartland Blvd.,
Brentwood, NY 11717
800.437.2826 631.243.2022
Fax 631.243.2027

