



12 watt T8 LED; Medium bi-pin base; 3000K; 50000 average rated hours; 1400 lumens

- All glass tube
- Direct wire 120-277V line voltage*
- NSF Approved
- No ballast or external driver required
- Built-in shock resistant circuit - (not hot until both ends are installed)



*Existing wiring to both sockets can remain in place
*Will work on both shunted or non-shunted sockets

Item Number	UPC	Voltage	Watts	Fluorescent Equivalent	Lamp Shape	Base	ANSI Base	
S9926	045923099267	120-277	12	25W	T8	Medium Bi-Pin	G13	
Lamp Code	Dimmable/Non-Dimmable		Finish	MOL In Inches	MOD In Inches	Initial Lumens	Average Rated Hours	Kelvin Temp
12T8/LED/36-830/BP	Non-Dimmable		White	36"	1.00"	1400	50000	3000
Color	CRI	Beam Spread Deg	Pack	Package Type	RoHS Compliant	UL or ETL Listed	UL Classification	
Soft White	82	220	10	Box	Yes	Yes	cULus - Damp Location Rated	
Warranty								
5 Year Limited								



National Toll-Free:
800.43.SATCO
(800.437.2826)
www.satco.com

Distribution Centers:
New York, Florida, Texas,
Washington, California,
Puerto Rico

Corporate Offices:
110 Heartland Blvd.,
Brentwood, NY 11717
800.437.2826 631.243.2022
Fax 631.243.2027



©2012, Satco Products, Inc. Not responsible for typographical errors. 06/12 S1051