



S9933

15T8U6/LED/22.5-850/BP
 15 watt T8 U-Bend LED; Medium bi-pin base; 5000K; 50000 average rated hours; 1800 lumens



Features

- No ballast or external driver required
- Direct wire 120-277V line voltage*
- Single-ended wiring
- All glass tube
- NSF Approved

* Install only in non-shunted lampholders

S9933

Item Number	UPC	Watts	Operating Frequency	Lamp Shape	Base	ANSI Base	Lamp Code
S9933	045923099335	15	50/60Hz	T8	Medium Bi-Pin	2G13	15T8U6/LED/22.5-850/BP
Dimmable/Non-Dimmable	Finish	MOL In Inches	MOD In Inches	Leg Spacing	Initial Lumens	Average Rated Hours	Kelvin Temp
Non-Dimmable	White	22.5"	7.00"	6"	1800	50000	5000
Color	CRI	Beam Spread Deg	Operating Temperature	Pack	Package Type	CEC Status	DLC ID:
Natural Light	82	220	-20C (-4F) to a maximum of +45C (+113F)	12	Box	Lawful for sale in California	PR2J7GTN DLC Search
RoHS Compliant	UL or ETL Listed	UL Classification			Warranty		
Yes	Yes	cULus Classified - Damp Location Rated			5 Year Limited		



National Toll-Free:
800.43.SATCO
(800.437.2826)
www.satco.com

Distribution Centers:
New York, Florida, Texas,
Washington, California,
Puerto Rico

Corporate Offices:
110 Heartland Blvd.,
Brentwood, NY 11717
800.437.2826 631.243.2022
Fax 631.243.2027

