



S9934

11.5T8/LED/48-830/DR
 11.5 watt T8 LED; Medium bi-pin base; 3000K; 50000 average rated hours; 1700 lumens

Features

- Direct Replacement - for use on Instant Start and Rapid Start ballasts with no rewiring required*
- Solid State LED lighting
- High efficacy
- DLC Qualified
- Compatible with emergency ballasts*
- All glass tube



S9934

*May not be compatible with all rapid start and emergency ballasts.

Ballast required

View:

[Ballast Compatibility Chart](#)

[Emergency Ballast Compatibility Chart](#)

Item Number	UPC	Watts	Fluorescent Equivalent	Lamp Shape	Base	ANSI Base	Lamp Code	
S9934	045923099342	11.5	25W-32W	T8	Medium Bi-Pin	G13	11.5T8/LED/48-830/DR	
Dimmable/Non-Dimmable	Finish	MOL In Inches	MOD In Inches	Initial Lumens	Average Rated Hours	Kelvin Temp	Color	
Non-Dimmable	White	48"	1.00"	1700	50000	3000	Soft White	
CRI	Beam Spread Deg	Pack	Package Type	DLC ID:	RoHS Compliant	UL or ETL Listed	UL Classification	
82	220	10	Box	PEM9VRFS DLC Search	Yes	Yes	cULus - Damp Location Rated	
Warranty								



National Toll-Free:
800.43.SATCO
(800.437.2826)
www.satco.com

Distribution Centers:
New York, Florida, Texas,
Washington, California,
Puerto Rico

Corporate Offices:
110 Heartland Blvd.,
Brentwood, NY 11717
800.437.2826 631.243.2022
Fax 631.243.2027

