

S9935

11.5T8/LED/48-835/DR 11.5 watt T8 LED; Medium bi-pin base; 3500K; 50000 average rated hours; 1700 lumens

Features

- Direct Replacement for use on Instant Start and Rapid Start ballasts with no rewiring required*
- Solid State LED lighting
- High efficacyDLC Qualified
- Compatible with emergency ballasts*
- All glass tube

S9935

*May not be compatible with all rapid start and emergency ballasts.

Ballast required

View: Ballast Compatibility Chart **Emergency Ballast Compatibility Chart**

Item Number	UPC		Watts	Fluorescent Equivalent		mp ape	Base	ANSI Base	La	mp Code
S9935	04592309	9359	11.5	25W-32W	T	8	Medium Bi- Pin	G13	11.5T8/LED/48-835/DR	
Dimmable/No	n-Dimmable	Finish	MOI Incł		. Initia	l Lumens	Average F Hours		Kelvin Temp	Color
Non-Dimmable		White	48	3" 1.00"		1700	50000		3500	Neutral White
	Spread eg Pa	ack Pao	ckage Ty	pe DLC ID:	Roł	IS Comp	liant UL or List		UL Cla	ssification

82	220	10	Box	P6HW61UD DLC Search	Yes	Yes	cULus - Damp Location Rated		
Warranty									
5 Year Limited									



National Toll-Free: 800.43.SATCO (800.437.2826) www.satco.com Distribution Centers: New York, Florida, Texas, Washington, California, Puerto Rico Corporate Offices: 110 Heartland Blvd., Brentwood, NY 11717 800.437.2826 631.243.2022 Fax 631.243.2027



@2012, Satco Products, Inc. Not responsible for typographical errors. 06/12 S1051