

## S9936

11.5T8/LED/48-840/DR 11.5 watt T8 LED; Medium bi-pin base; 4000K; 50000 average rated hours; 1800 lumens

## Features

- Direct Replacement for use on Instant Start and Rapid Start ballasts with no rewiring required\*
- Solid State LED lighting
- High efficacyDLC Qualified
- Compatible with emergency ballasts\*
- All glass tube

\*May not be compatible with all rapid start and emergency ballasts.

Ballast required

View:

**Ballast Compatibility Chart Emergency Ballast Compatibility Chart** 



S9936

Item Number	UPC	Watts	Fluorescent Equivalent	Lamp Shape	Base	ANSI Base	Lamp Code
S9936	045923099366	11.5	25W-32W	Т8	Medium Bi- Pin	G13	11.5T8/LED/48-840/DR

Dimmable/Non-Dimmable	Finish	MOL In Inches	MOD In Inches	Initial Lumens	Average Rated Hours	Kelvin Temp	Color
Non-Dimmable	White	48"	1.00"	1800	50000	4000	Cool White

CRI	Beam Spread Deg	Pack	Package Type	DLC ID:	RoHS Compliant	UL or ETL Listed	UL Classification
82	220	10	Вох	PTKCH997 DLC Search	Yes	Yes	cULus - Damp Location Rated

Warranty





National Toll-Free: 800.43.SATCO (800.437.2826) www.satco.com Distribution Centers: New York, Florida, Texas, Washington, California, Puerto Rico Corporate Offices: 110 Heartland Blvd., Brentwood, NY 11717 800.437.2826 631.243.2022 Fax 631.243.2027



@2012, Satco Products, Inc. Not responsible for typographical errors. 06/12 S1051