



11.5 watt T8 LED; Medium bi-pin base; 5000K; 50000 average rated hours; 1800 lumens

- Direct Replacement - for use on Instant Start and Rapid Start ballasts with no rewiring required*
- Solid State LED lighting
- High efficacy
- DLC Qualified
- Compatible with emergency ballasts*
- All glass tube


Ballast required

[Ballast Compatibility Chart](#)
[Emergency Ballast Compatibility Chart](#)



S9937

Item Number		UPC		Watts	Fluorescent Equivalent	Lamp Shape	Base	ANSI Base	Lamp Code
S9937		045923099373		11.5	25W-32W	T8	Medium Bi-Pin	G13	11.5T8/LED/48-850/DR
Dimmable/Non-Dimmable		Finish	MOL In Inches	MOD In Inches	Initial Lumens	Average Rated Hours		Kelvin Temp	Color
Non-Dimmable		White	48"	1.00"	1800	50000		5000	Natural Light
CRI	Beam Spread Deg	Pack	Package Type	DLC ID:	RoHS Compliant	UL or ETL Listed	UL Classification		
82	220	10	Box	PA4P1QV4 DLC Search	Yes	Yes	cULus - Damp Location Rated		
Warranty									



National Toll-Free:
800.43.SATCO
(800.437.2826)
www.satco.com

Distribution Centers:
New York, Florida, Texas,
Washington, California,
Puerto Rico

Corporate Offices:
110 Heartland Blvd.,
Brentwood, NY 11717
800.437.2826 631.243.2022
Fax 631.243.2027

