

## S29312

9.8WLED/RDL/5-6/27K/12 9.8 watt LED Downlight Retrofit; 5 - 6"; 2700K; Dimmable; 120

## Features

- Solid State LED lighting
  Downlight Retrofit
  Long life
  Dimmable

- E26 adapter included

This retrofit is for use with recessed housings with an E26 socket only



S29312

| Item<br>Number            | UPC                                |              | Voltage                          | \/\/atte |                    | andescent<br>quivalent                |      | Fixture<br>Type      |             | Base     | L                      | Lamp Code                 |                |  |
|---------------------------|------------------------------------|--------------|----------------------------------|----------|--------------------|---------------------------------------|------|----------------------|-------------|----------|------------------------|---------------------------|----------------|--|
| S29312                    | 045                                | 045923293122 |                                  | 9.8      | 65W                |                                       |      | Retrofit Co          |             | onnector |                        | .8WLED/RDL/5-<br>6/27K/12 |                |  |
| Dimmable/Non-<br>Dimmable |                                    | Sugg         | uggested Dimmers                 |          | Finish             | MOL In<br>Inches                      |      | MOD In<br>Inches     | Init<br>Lum |          | Average Rated<br>Hours |                           | Kelvin<br>Temp |  |
| Dimmable                  |                                    |              | Compatible dimmers<br>for S29312 |          | rosted             | 2-5/16"                               |      | 7-3/8"               | 650         |          | 35000                  |                           | 2700           |  |
| Color                     | CRI Beam Spread Operating Temperat |              |                                  |          |                    | ture I                                | Pack | k Package Type ENERG |             |          | GY STAR                | Y STAR CEC Status         |                |  |
| Warm<br>White             | 90                                 | 90           | -20C (                           | . ,      | a maxim<br>(+104F) | um of                                 | 12   | Box                  |             | ENER     | ENERGY STAR            |                           | Non-Compliant  |  |
| RoHS (                    | Complia                            | ant          | UL or ETL Listed                 |          |                    | UL Classification                     |      |                      |             |          | Warranty               |                           |                |  |
| `                         | Yes                                |              | Yes                              |          |                    | cULus Classified - Wet Location Rated |      |                      |             |          |                        | 5 Year Limited            |                |  |



National Toll-Free: 800.43.SATCO (800.437.2826) www.satco.com Distribution Centers: New York, Florida, Texas, Washington, California, Puerto Rico Corporate Offices: 110 Heartland Blvd., Brentwood, NY 11717 800.437.2826 631.243.2022 Fax 631.243.2027



©2012, Satco Products, Inc. Not responsible for typographical errors. 06/12 S1051