



S29675

80W/LED/HID/4000K/100-277V/EX39

80 watt - LED HID Replacement; 4000K; Mogul extended base;
100-277 volts

Features

- High Lumen Omni-directional LED for Industrial / Commercial applications
- Replaces HID, CFL, and Incandescent
- Ballast by-pass - Direct wire only 100V - 277V
- UL approved for totally enclosed fixtures
- Damp location - IP65 rated
- For outdoor & indoor use
- DLC Listed
- Base up or base down operation (high/low bay and post top)
- Emits no UV light / Contains no mercury (Hg)
- Built-in surge protection - 5KV
- 5 year limited warranty
- Classified under UL 1598C
- Safety chain included

Additional Technical Specifications

- Power Factor >0.9
- Operating temperature range -20°C to 65°C
- Operating Frequency 50-60Hz
- Working Voltage AC90-305V
- Built in surge protection

Minimum Compartment Size		
Length	Width	Depth
17.3 inch	9.25 inch	9.25 inch

Optional accessory: In-line surge protector [80-929](#)



S29675

Item Number	Product Line	UPC	Input Voltage	Watts	Operating Frequency	Incandescent Equivalent	Fluorescent Equivalent
S29675	Hi-Pro	045923296758	100 - 277	80	50/60Hz	400W	100W

HID Equivalent	Base	ANSI Base	Lamp Code	Dimmable/Non-Dimmable	Finish	MOL In Inches	MOD In Inches
----------------	------	-----------	-----------	-----------------------	--------	---------------	---------------

320W	Mogul Extended	EX39	80W/LED/HID/4000K/100-277V/EX39			Non-Dimmable	White	9-1/4"	5.87"
Initial Lumens	Average Rated Hours	Kelvin Temp	Color	CRI	Beam Spread Deg	Operating Temperature			Pack
10400	50000	4000	Cool White	80+	300	-20C (-4F) to a maximum of +65C (+149F)			4
Package Type	CEC Status	DLC ID:		RoHS Compliant	UL Classification		Warranty	Thermal Management	
Box	Lawful for sale in California	PL4G04M6FSXL DLC Search		Yes	cULus - Wet Location Rated		5 Year Limited	More Details About	



National Toll-Free:
800.43.SATCO
(800.437.2826)
www.satco.com

Distribution Centers:
New York, Florida, Texas,
Washington, California,
Puerto Rico

Corporate Offices:
110 Heartland Blvd.,
Brentwood, NY 11717
800.437.2826 631.243.2022
Fax 631.243.2027



©2012, Satco Products, Inc. Not responsible for typographical errors. 06/12 S1051