

S29677

120W/LED/HID/4000K/100-277V/EX39 120 watt - LED HID Replacement; 4000K; Mogul extended base; 100-277 volts

Features

- High Lumen Omni-directional LED for Industrial / Commercial applications
- Replaces HID, CFL, and Incandescent
 Ballast by-pass Direct wire only 100V 277V
- UL approved for totally enclosed fixtures
 Damp location IP65 rated
- For outdoor & indoor use
- DLC Listed
- Base up or base down operation (high/low bay and post top)
- Emits no UV light / Contains no mercury (Hg)
- Built-in surge protection 5KV
- 5 year limited warranty
- Classified under UL 1598C
- · Safety chain included

Additional Technical Specifications

- Power Factor >0.9
- Operating temperature range -20°C to 65°C
- Operating Frequency 50-60Hz
- Working Voltage AC90-305V
- Built in surge protection

Minimum Compartment Size							
Length	Width	Depth					
17.3 inch	9.25 inch	9.25 inch					

Optional accessory: In-line surge protector 80-929



220	677
029	0/1

Item	Product	UPC	Input		Operating	Incandescent	Fluorescent	
Number	Line		Voltage Watts		Frequency	Equivalent	Equivalent	
S29677	Hi-Pro	045923296772	100 - 277	120	50/60Hz	750W	200W	

HID	Door	ANSI	Lamp Cada	Dimmable/Non-	Finish	MOL In	MOD In
Equivalent	Base	Base	Lamp Code	Dimmable	Finish	Inches	Inches

600W	Mogul Extended	E X.39		120W/LED/HID/4000K/100- 277V/EX39		Non-Dimmable		White	10-3/8"	5-7/8"		
Initial Lumen	Average Ra s Hours	ted Ke	Kelvin Temp Color		CRI		n Spread Operating Temperat		perature	Pack		
15600	50000		4000	Cool White	80+	;	300	-20C (-4F) to a m +65C (+1			4	
Package Type	CEC Status		DLC ID:		RoHS Compli		UL Classification		Warranty		ermal gement	
Вох	Lawful for sale in California	PLGH7	PL1YPC7YDO1H; PLGH793AQSRY DLC Search		Yes	;	cULus - Wet Location Rated		5 Year Limited		More Details About	

120W/LED/HID/4000K/100-



National Toll-Free: 800.43.SATCO (800.437.2826) www.satco.com

Mogul

Distribution Centers: New York, Florida, Texas, Washington, California, Puerto Rico

Corporate Offices: 110 Heartland Blvd., Brentwood, NY 11717 800.437.2826 631.243.2022 Fax 631.243.2027



©2012, Satco Products, Inc. Not responsible for typographical errors. 06/12 S1051