

S8706

25WLED/CDL/6/4K/100-277 25 watt Commercial LED Downlight Retrofit; 6 inch; 4000K; 100-277 volts

Features

- Solid State LED lighting
 External driver for simple retrofitting
 Quick connect feature for easy installation
- 100-277 range voltage circuit
- 0-10V dimming



80-937 6" mounting plate for commercial recessed downlights.



S8706

	Item UPC Number		Voltage W		Operating Frequency		Fixture Ba		se L		Lamp Code		
S87	706 0459	23087066	100-277	25	50/60Hz		Retrofit	Conn	ector	25WLED/CDL/6/4k		6/4K/	100-277
Dimmable/Non- Dimmable		Sugg	Suggested Dimmers		MOL In Inches	MOD I Inche		Initial Lumens		ge Rated Kelvi lours Terr			Color
0-10V Dimming Only		1lv	Compatible dimmers for S8706		7-1/2"	7-1/2	" 1	1900		50000		0	Cool White
CRI	CRI Operating Temperature			RGY AR	CEC Status		Rol Com _l		UL Classification		ion	Warranty	
90	-20C (-4F) to +45C		RGY AR	Lawful for sale in California		Ye	es	cULus - Wet Loc Rated		ation	5 Year Limited		





Distribution Centers: New York, Florida, Texas, Washington, California, Puerto Rico

Corporate Offices: 110 Heartland Blvd., Brentwood, NY 11717 800.437.2826 631.243.2022 Fax 631.243.2027

