S8928

20W/LED/HID/WP/5K/E26/100-277V
20 watt LED Hi-lumen, omni-directional lamp for commercial fixture applications; 5000K; Medium base; 100-277 volts

Features
- High Lumen Omni-directional LED for for use in wall pack, canopy, shoe box, or cobra head fixture
- Replaces HID, CFL, and Incandescent
- Ballast by-pass - Direct wire only 100V - 277V
- UL approved for totally enclosed fixtures
- Horizontal operation
- Emits no UV light / Contains no mercury (Hg)
- 5 year limited warranty
- cULus listed

S8928

Minimum Compartment Size		
Length	Width	Depth
8.5 inch	6 inch	6 inch

Optional accessory: In-line surge protector 80-929

Item Number	Product Line	UPC	Input Voltage	Watts	Operating Frequency	HID Equivalent	Base
S8928	Hi-Pro	045923089282	100 - 277	20	50/60Hz	100W	Medium

ANSI Base	Lamp Code	Dimmable/Non-Dimmable	Finish	MOL In Inches	MOD In Inches	Initial Lumens	Average Rated Hours
E26	20W/LED/HID/WP/5K/E26/100-277V	Non-Dimmable	White	5-5/16"	3-1/8"	3000	50000

Kelvin Temp	Color	CRI	Beam Spread Deg	Operating Temperature	Pack	Package Type	CEC Status
5000	Natural Light	80+	180	-40C (-40F) to a maximum of +60C (+140F)	24	Box	Lawful for sale in California

RoHS Compliant	UL or ETL Listed	UL Classification	Warranty
Yes	Yes	cULus - Damp Location Rated	5 Year Limited