


T12 Med Bipin



Circline 4-Pin T9



T12 RDC

RAPID START LAMPS**CURVALUME® Rapid Start SUPERSAVER® - U-Shaped, 6" Leg Spacing**

Nominal Wattage	Bulb	Nominal Length (in)	MOL (in)	Base	Product Number	Ordering Abbreviation	Pkg Qty	Avg Rated Life (hrs)	CCT (K)	CRI	Approx Lumens Initial @25°C/77°F	Mean	Symbols & Footnotes
34	T12	22.5	22.6	Med Bipin	24059	FB34/CW/6/SS/UPC <i>formerly FB40/CW/SS/6</i>	12	18000	4200	62	2600	2236	Ⓢ 1,2,43,45

CURVALUME® Rapid Start Standard Lamps - U-Shaped, 6" Leg Spacing

Nominal Wattage	Bulb	Nominal Length (in)	MOL (in)	Base	Product Number	Ordering Abbreviation	Pkg Qty	Avg Rated Life (hrs)	CCT (K)	CRI	Approx Lumens Initial @25°C/77°F	Mean	Symbols & Footnotes
40	T12	22.5	22.6	Med Bipin	24080	FB40/D30/6	12	18000	3000	70	3050	2745	Ⓢ 1,2,8,43
					24017	FB40/D830/6	12	18000	3000	80	3200	2880	Ⓢ 1,2,8,43
					24081	FB40/D35/6	12	18000	3500	70	3050	2745	Ⓢ 1,2,8,43
					24004	FB40/CWX/6	12	18000	4100	87	2100	1806	1,2,8,43
					24082	FB40/D41/6	12	18000	4100	70	3050	2745	Ⓢ 1,2,8,43

Circline T9 Rapid Start Lamps

Nominal Wattage	Bulb	Outside Diameter (in)	Base	Product Number	Ordering Abbreviation	Pkg Qty	Avg Rated Life (hrs)	CCT (K)	CRI	Approx Lumens Initial @25°C/77°F	Mean	Symbols & Footnotes
20	T9	6.25-6.75	4 Pin	20155	FC6T9/WW/RS	12	8000	3000	52	800	696	1,2,8,48
				20156	FC6T9/CW/RS	12	8000	4200	62	750	653	1,2,8,48
22	T9	8.00-8.50	4 Pin	20209	FC8T9/DWW/RP	6	12000	3000	70	1100	990	1,2,8,48
				20088	FC8T9/WW/RS	12	12000	3000	52	1050	914	1,2,8,48
				20148	FC8T9/CW/RS	12	12000	4200	62	1050	914	1,2,8,48
				20151	FC8T9/CW/RS/6 PACK	6	12000	4200	62	1050	914	1,2,8,48
				20080	FC8T9/D/RS	12	12000	6500	76	900	783	1,2,8,48
30	T9	8.00-8.50	4 Pin	20210	FC8T9/830/EL	6	10000	3000	80	1850	1591	1,2,3,16,17,49
32	T9	11.50-12.0	4 Pin	20233	FC12T9/DWW/RP	6	15000	3000	70	2100	1806	1,2,8,48
				20037	FC12T9/WW/RS	12	15000	3000	52	1950	1697	1,2,8,48
				20142	FC12T9/CW/RS	12	15000	4200	62	1925	1675	1,2,8,48
				20143	FC12T9/CW/RS/6 PACK	6	15000	4200	62	1925	1675	1,2,8,48
				20030	FC12T9/D/RS	12	15000	6500	76	1650	1436	1,2,8,48
40	T9	15.5-16	4 Pin	20057	FC16T9/WW/RS	12	18000	3000	52	2800	2436	1,2,8,48
				20132	FC16T9/CW/RS	12	18000	4200	62	2750	2393	1,2,8,48
				20072	FC16T9/D/RS	12	18000	6500	76	2350	2045	1,2,8,48

High Output (800mA) Rapid Start SUPERSAVER® Lamps

Nominal Wattage	Bulb	Nominal Length (in)	MOL (in)	Base	Product Number	Ordering Abbreviation	Pkg Qty	Avg Rated Life (hrs)	CCT (K)	CRI	Approx Lumens Initial @25°C/77°F	Mean	Symbols & Footnotes
55	T12	48	46	Recessed DC	25137	F48T12D35/HO/SS	30	12000	3500	70	3750	3375	1,2,50,51
95	T12	96	93.91	Recessed DC	25008	F96T12/D830/HO/SS	15	12000	3000	80	8750	8050	Ⓢ 1,2,50,51
					25011	F96T12/WW/HO/SS	15	12000	3000	52	7700	6237	Ⓢ 1,2,50,51