

**Product Number:** 49473

**Order Abbreviation:** QHE 2X32T8/347 ISL-SC

**General Description:** 2-lamp 32wT8 High Efficiency Instant start electronic ballast, 347V, low ballast factor, 10-pk



### Product Information

|                                   |                               |
|-----------------------------------|-------------------------------|
| Abbrev. With Packaging Info.      | QHE2X32T8347ISLSC 10/CS 1/SKU |
| Ballast Factor                    | 0.78                          |
| Ballast Height H (in)             | 1.1810                        |
| Ballast Length L (in)             | 9.4690                        |
| Ballast Width W (in)              | 1.6810                        |
| Circuit Type                      | Parallel                      |
| Family Brand Name                 | QUICKTRONIC High-Efficiency   |
| Input Current (Amps)              | 0.00                          |
| Nominal Voltage (V)               | 347V                          |
| Number of Lamps                   | 2                             |
| Open Circuit Voltage (V)          | <600V                         |
| Power Factor                      | >0.97                         |
| Primary Lamp Type                 | FO32/XP                       |
| Sound Rating                      | A                             |
| Starting Method                   | Instant Start                 |
| Starting Temperature - Fahrenheit | -20                           |
| Starting Temperature - Celsius    | -29                           |
| Total Harmonic Distortion (THD)   | <10%                          |
| Wiring Method                     | Leads                         |
| Max Case Temperature              | 70°C                          |



### Footnotes

- Data based on primary lamp types. See LEDVANCE System Performance Guide for data on other lamp combinations.
- Remote Mounting up to 18 feet
- 70C Max Case Temperature
- UL Listed Class P, Type 1 Outdoor
- Insulate unused leads

- Ground ballast case
- Lampholder must be shorted per diagram
- Install in accordance with National Electric Codes
- Complies with FCC 47 CFR Part 18, Non-Consumer
- ANSI 62.41 Cat. A Transient Protection
- Class A Sound Rating.
- Wiring diagram applies to instant start standard, low power (LP), PLUS, and HD10 ballast types.
- High power factor
- Minimum starting temperature: 60 F / 16 C with SS lamps
- Minimum starting temperature: -20 F / -29 C
- FCC 47 CFR part 15, Class A
- Insulate unused leads individually for 600V