Product Details 4/6/21, 12:12 PM



Product 64264 **Number:**

Order MCP39/PAR20/U/830/SP PB

Abbreviation:

General 39W high CRI, powerball arc tube, reduced color shift, high performance, open rated, Par 20

Description: Metal Halide Lamp, spot

Product Information

Abbrev. With Packaging Info. MCP39PAR20U830SPPB 12/CS 1/SKU

ANSI Code C130/O
Approx. Lumens (initial - horizontal) 2000
Average Rated Life - Horizontal (hr) 12000
Average Rated Life - (hr) 12000
Average Rated Life - Vertical (hr) 12000

Base E26 Medium

Beam Angle (deg) 10
Beam Type SP
Bulb PAR20
Color Temperature/CCT (K) 3000
Diameter (in) 2.480
Diameter (mm) 63.00

Family Brand Name Metalarc® Powerball

Lamp Finish Clear Nominal Voltage (V) 90.00 Nominal Wattage (W) 39.00





Footnotes

- Consult your LEDVANCE Lighting Representative for compatible electronic operating systems.
- Use with 4000V pulse rated sockets only.
- O = Lamps classified as O-type, comply with ANSI standard C78.389 for containment testing and may be used in open luminaries. See lamp warning.
- The circuit must include overcurrent protection (I.e. Thermally switched ballast).
- Lamp requires a nominal Open Circuit Voltage of 230V or higher. Without an ignitor in the circuit minimum OCV is 209Vrms.
- UV-Stop quartz
- Approved electronic ballast is required, view approved ballast list in Product documents, graphs and images.

Product Details 4/6/21, 12:12 PM