

[Return to search](#)[Print Page](#)

**Product Number:** 67533  
**Order Abbreviation:** LU400/ECO  
**General Description:** 400W mogul based, environmentally friendlier general lighting high pressure sodium lamp, clear, universal burn

#### Product Information

Abbrev. With Packaging Info.	LU400ECO 20/CS 1/SKU
ANSI Code	S51
Approx. Lumens (initial - horizontal)	50000
Approx. Lumens (initial - vertical)	50000
Approx. Lumens (mean - horizontal)	45000
Approx. Lumens (mean - vertical)	45000
Arc Length (in)	3.19
Arc Length (mm)	81
Avg Rated Life (hrs)	24000+
Base	E39 Mogul
Bulb	ET18
Color Rendering Index (CRI)	22
Color Temperature/CCT (K)	2100
Diameter (in)	2.2
Diameter (mm)	57
Family Brand Name	Lumalux® ECO
Fixture Requirement	0
Hot Restrike Time (min)	1 MIN
Lamp Finish	Clear
Light Center Length - LCL (in)	5.75
Light Center Length - LCL (mm)	146
Maximum Base Temperature - Fahrenheit	482
Maximum Base Temperature - Celsius	250
Maximum Bulb Temperature - Fahrenheit	752

Maximum Bulb Temperature - Celsius	400
Maximum Overall Length - MOL (in)	9.75
Maximum Overall Length - MOL (mm)	247.6
Nominal Voltage (V)	100.00
Nominal Wattage (W)	400.00
Operating Position	Universal
Time to Stabilization (minutes)	3-4 MINUTES

#### Additional Product Information

##### **Product Documents, Graphs, and Images**

##### **Compatible Ballast**

##### **Packaging Information**



#### Footnotes

- Use with 4000V pulse rated sockets only.
- Passes Federal TCLP test based on NEMA LL Series Standards. TCLP data available upon request. Disposal regulations may vary depending on location. Please check your local and state/provincial regulations.
- Mean lumens measured at 50% of average rated life

[Print Page](#)