M3912CK-6EUN-F

APPLICATION and PERFORMANCE SPECIFICATION

Description: Mini Slim Case - electronic low frequency square wave ballast for 39W metal halide lamps

- Line Voltage: 120vac , ±10%, 50/60Hz
- Microprocessor controlled
- RoHS Compliant
- Mounting type: Feet - side lead exit

- Resonance Start
- Active power factor correction
- Abnormal operation shutdown circuit: Line voltage must be reset

*60 Hz data

Lamp		Volts	Input	Nominal	Power	Ballast	Harmonic	Crest
ANSI Type	#		Watts	Line Amps	Factor	Factor	Total	Factor
M130/C130	**1**	**120**	**45**	**0.38**	**> 95%**	**1.00**	**<5%**	**<1.5**

Ballast Order Code: 188246

Performance:
- Meets ANSI Standard C82.14-2006
- Meets ANSI Standard C62.41-1991
- Meets FCC Part 18C for EMI & RFI (non-consumer)
- EOL Protection

Safety:
- No PCBs
- $_{C}UL_{US}$ Listed (Outdoor Type 1)
- Thermal Protection

Application:
- Minimum Starting Temperature: -15°C/+5°F
- Maximum Case Temperature: 85°C/ 185°F
- Sound Rated: A
- Remote Mounting: 10 feet

Each lamp's lead wires must be run in a separate minimum 1/2" ID conduit from the input leads to achive good EMI performance and maximum remote capabilities. Individual , unbundled lead wires must be used for extension wiring using wire types SF-2 or SFF-2 or equivalent. Power cords and MC cables are not acceptable extension wiring methods.

Physical Parameters

	Inches/Metric
Overall Length:	5.51"/140mm
Width:	1.17"/44.5mm
Height:	1.18"/30.0mm
Weight:	8 oz
Lead lengths: All	10"/254mm
Lead stripping:(Tinned) All	.375"/9.53mm

Warranty:

Universal Lighting Technologies warrants to the purchaser that each electronic ballast will be free from defects in material or workmanship for a period of 3 years from date of manufacture when properly installed and under normal conditions of use. The normal operation of 4000 hr./yr. is used for the warranty period. Longer operating times will adjust the warranty period accordingly. For extended warranty periods greater than 36 months, **call 1-800 BALLAST** for fixture testing instructions.

Manufactured in Japan



