

WAC LIGHTING

Ice Cube

Round Multi Light 4CCT

Model & Size	Color Temp & CRI	Watt	Lumens	Finish
☐ PD-29303R 8" - 3 Lights	2700K/3000K/3500K/4000K - 90	21 W	1130	☐ AB Aged Brass ☐ BK Black

Fixture Type: _____

Catalog Number: _____

Project: _____

Location: _____

Example: **PD-29303R-BK**

For custom requests please contact customs@waclighting.com

DESCRIPTION

Faceted like a hand-cut jewel, adding a dash of chic to a room's ensemble.

FEATURES

- K9 crystal
- Low profile, adjustable powered aircraft cables for an ultra-clean look
- Built in color temperature adjustability. Switch from 2700K/3000K/3500K/4000K
- NEC CODE (314.24) requires that ceiling outlet boxes in the U.S. support up to 50 lbs.
- This fixture in the 9, 15 & 21 light format exceeds 50 lbs. and must be installed adequately on the ceiling with weight distributed evenly on the mounting backplate.
- Driver concealed within the canopy

SPECIFICATIONS


Color Temp:	2700K/3000K/3500K/4000K
Input:	120-277V, 50/60Hz
CRI	90
Dimming:	ELV: 100-10%, 0-10V: 100-5%, TRIAC: 100-5%
Rated Life:	50,000 Hours
Standards:	ETL, cETL, Damp Location Listed
Construction	Steel frame with K9 crystal diffuser

REPLACEMENT PARTS

RPL-GLA-29308 - PD-29308 Crystal




FINISHES:



Aged Brass

Black

LINE DRAWING:



WAC LIGHTING

Ice Cube

Round Multi Light 4CCT

Model & Size	Color Temp & CRI	Watt	Lumens	Finish
☐ PD-29305R 8" - 5 Lights	2700K/3000K/3500K/4000K - 90	36 W	1930	☐ AB Aged Brass ☐ BK Black

Fixture Type: _____

Catalog Number: _____

Project: _____

Location: _____

Example: **PD-29305R-BK**

For custom requests please contact customs@waclighting.com

DESCRIPTION

Faceted like a hand-cut jewel, adding a dash of chic to a room's ensemble.

FEATURES

- K9 crystal
- Low profile, adjustable powered aircraft cables for an ultra-clean look
- Built in color temperature adjustability. Switch from 2700K/3000K/3500K/4000K
- NEC CODE (314.24) requires that ceiling outlet boxes in the U.S. support up to 50 lbs.
- This fixture in the 9, 15 & 21 light format exceeds 50 lbs. and must be installed adequately on the ceiling with weight distributed evenly on the mounting backplate.
- Driver concealed within the canopy

SPECIFICATIONS


Color Temp:	2700K/3000K/3500K/4000K
Input:	120-277V, 50/60Hz
CRI	90
Dimming:	ELV: 100-10%, 0-10V: 100-5%, TRIAC: 100-5%
Rated Life:	50,000 Hours
Standards:	ETL, cETL, Damp Location Listed
Construction	Steel frame with K9 crystal diffuser

REPLACEMENT PARTS


RPL-GLA-29308 - PD-29308 Crystal



FINISHES:



LINE DRAWING:



WAC LIGHTING

Ice Cube

Round Multi Light 4CCT

Model & Size	Color Temp & CRI	Watt	Lumens	Finish
☐ PD-29309R 8" - 9 Lights	2700K/3000K/3500K/4000K - 90	65 W	3515	☐ AB Aged Brass ☐ BK Black

Fixture Type: _____

Catalog Number: _____

Project: _____

Location: _____

Example: **PD-29309R-BK**

For custom requests please contact customs@waclighting.com

DESCRIPTION

Faceted like a hand-cut jewel, adding a dash of chic to a room's ensemble.

FEATURES

- K9 crystal
- Low profile, adjustable powered aircraft cables for an ultra-clean look
- Built in color temperature adjustability. Switch from 2700K/3000K/3500K/4000K
- NEC CODE (314.24) requires that ceiling outlet boxes in the U.S. support up to 50 lbs.
- This fixture in the 9, 15 & 21 light format exceeds 50 lbs. and must be installed adequately on the ceiling with weight distributed evenly on the mounting backplate.
- Driver concealed within the canopy

SPECIFICATIONS


Color Temp:	2700K/3000K/3500K/4000K
Input:	120-277V, 50/60Hz
CRI	90
Dimming:	ELV: 100-10%, 0-10V: 100-5%, TRIAC: 100-5%
Rated Life:	50,000 Hours
Standards:	ETL, cETL, Damp Location Listed
Construction	Steel frame with K9 crystal diffuser

REPLACEMENT PARTS

RPL-GLA-29308 - PD-29308 Crystal




FINISHES:



Aged Brass

Black

LINE DRAWING:



WAC LIGHTING

Ice Cube

Round Multi Light 4CCT

Model & Size	Color Temp & CRI	Watt	Lumens	Finish
☐ PD-29315R 8" - 15 Lights	2700K/3000K/3500K/4000K - 90	108 W	5780	☐ AB Aged Brass ☐ BK Black

Fixture Type: _____

Catalog Number: _____

Project: _____

Location: _____

Example: **PD-29315R-BK**

For custom requests please contact customs@wacighting.com

DESCRIPTION

Faceted like a hand-cut jewel, adding a dash of chic to a room's ensemble.

FEATURES

- K9 crystal
- Low profile, adjustable powered aircraft cables for an ultra-clean look
- Built in color temperature adjustability. Switch from 2700K/3000K/3500K/4000K
- NEC CODE (314.24) requires that ceiling outlet boxes in the U.S. support up to 50 lbs.
- This fixture in the 9, 15 & 21 light format exceeds 50 lbs. and must be installed adequately on the ceiling with weight distributed evenly on the mounting backplate.
- Driver concealed within the canopy

SPECIFICATIONS


Color Temp:	2700K/3000K/3500K/4000K
Input:	120-277V, 50/60Hz
CRI	90
Dimming:	ELV: 100-10%, 0-10V: 100-5%, TRIAC: 100-5%
Rated Life:	50,000 Hours
Standards:	ETL, cETL, Damp Location Listed
Construction	Steel frame with K9 crystal diffuser

REPLACEMENT PARTS


RPL-GLA-29308 - PD-29308 Crystal



FINISHES:



LINE DRAWING:



WAC LIGHTING

Ice Cube

Round Multi Light 4CCT

Model & Size	Color Temp & CRI	Watt	Lumens	Finish
☐ PD-29321R 8" - 21 Lights	2700K/3000K/3500K/4000K - 90	150 W	8060	☐ AB Aged Brass ☐ BK Black

Fixture Type: _____

Catalog Number: _____

Project: _____

Location: _____

Example: **PD-29321R-BK**

For custom requests please contact customs@waclighting.com

DESCRIPTION

Faceted like a hand-cut jewel, adding a dash of chic to a room's ensemble.

FEATURES

- K9 crystal
- Low profile, adjustable powered aircraft cables for an ultra-clean look
- Built in color temperature adjustability. Switch from 2700K/3000K/3500K/4000K
- NEC CODE (314.24) requires that ceiling outlet boxes in the U.S. support up to 50 lbs.
- This fixture in the 9, 15 & 21 light format exceeds 50 lbs. and must be installed adequately on the ceiling with weight distributed evenly on the mounting backplate.
- Driver concealed within the canopy

SPECIFICATIONS


Color Temp:	2700K/3000K/3500K/4000K
Input:	120-277V, 50/60Hz
CRI	90
Dimming:	ELV: 100-10%, 0-10V: 100-5%, TRIAC: 100-5%
Rated Life:	50,000 Hours
Standards:	ETL, cETL, Damp Location Listed
Construction	Steel frame with K9 crystal diffuser

REPLACEMENT PARTS

RPL-GLA-29308 - PD-29308 Crystal



FINISHES:



LINE DRAWING:

