

WAC LIGHTING

Ice Cube

Square Multi Light 4CCT

Model & Size	Color Temp & CRI	Watt	Lumens	Finish
☐ PD-29313S 8" - 13 Lights	2700K/3000K/3500K/4000K - 90	93 W	4970	☐ AB Aged Brass ☐ BK Black

Example: **PD-29313S-BK**

For custom requests please contact customs@waclighting.com

DESCRIPTION

Faceted like a hand-cut jewel, adding a dash of chic to a room's ensemble.

FEATURES

- K9 crystal
- Low profile, adjustable powered aircraft cables for an ultra-clean look
- Built in color temperature adjustability. Switch from 2700K/3000K/3500K/4000K
- NEC CODE (314.24) requires that ceiling outlet boxes in the U.S. support up to 50 lbs.
- This fixture in the 23 light format exceeds 50 lbs. and must be installed adequately on the ceiling with weight distributed evenly on the mounting backplate.
- Driver concealed within the canopy

SPECIFICATIONS

Color Temp:	2700K/3000K/3500K/4000K
Input:	120-277V, 50/60Hz
CRI	90
Dimming:	ELV: 100-10%, 0-10V: 100-5%, TRIAC: 100-5%
Rated Life:	50,000 Hours
Standards:	ETL, cETL, Damp Location Listed
Construction	Steel frame with K9 crystal diffuser

REPLACEMENT PARTS

RPL-GLA-29308 - PD-29308 Crystal

Fixture Type: _____

Catalog Number: _____

Project: _____


Location: _____



FINISHES:



LINE DRAWING:



WAC LIGHTING

Ice Cube

Square Multi Light 4CCT

Model & Size	Color Temp & CRI	Watt	Lumens	Finish
☐ PD-29325S 8" - 25 Lights	2700K/3000K/3500K/4000K - 90	180 W	9640	☐ AB Aged Brass ☐ BK Black

Example: **PD-29325S-BK**

For custom requests please contact customs@waclighting.com

DESCRIPTION

Faceted like a hand-cut jewel, adding a dash of chic to a room's ensemble.

FEATURES

- K9 crystal
- Low profile, adjustable powered aircraft cables for an ultra-clean look
- Built in color temperature adjustability. Switch from 2700K/3000K/3500K/4000K
- NEC CODE (314.24) requires that ceiling outlet boxes in the U.S. support up to 50 lbs.
- This fixture in the 23 light format exceeds 50 lbs. and must be installed adequately on the ceiling with weight distributed evenly on the mounting backplate.
- Driver concealed within the canopy

SPECIFICATIONS

Color Temp:	2700K/3000K/3500K/4000K
Input:	120-277V, 50/60Hz
CRI	90
Dimming:	ELV: 100-10%, 0-10V: 100-5%, TRIAC: 100-5%
Rated Life:	50,000 Hours
Standards:	ETL, cETL, Damp Location Listed
Construction	Steel frame with K9 crystal diffuser

REPLACEMENT PARTS

RPL-GLA-29308 - PD-29308 Crystal

Fixture Type: _____

Catalog Number: _____

Project: _____

Location: _____




FINISHES:



Aged Brass

Black

LINE DRAWING:



WAC LIGHTING

Ice Cube

Square Multi Light 4CCT

Model & Size	Color Temp & CRI	Watt	Lumens	Finish
☐ PD-29341S 8" - 41 Lights	2700K/3000K/3500K/4000K - 90	294 W	15870	☐ AB Aged Brass ☐ BK Black

Example: **PD-29341S-BK**

For custom requests please contact customs@waclighting.com

DESCRIPTION

Faceted like a hand-cut jewel, adding a dash of chic to a room's ensemble.

FEATURES

- K9 crystal
- Low profile, adjustable powered aircraft cables for an ultra-clean look
- Built in color temperature adjustability. Switch from 2700K/3000K/3500K/4000K
- NEC CODE (314.24) requires that ceiling outlet boxes in the U.S. support up to 50 lbs.
- This fixture in the 23 light format exceeds 50 lbs. and must be installed adequately on the ceiling with weight distributed evenly on the mounting backplate.
- Driver concealed within the canopy

SPECIFICATIONS

Color Temp:	2700K/3000K/3500K/4000K
Input:	120-277V, 50/60Hz
CRI	90
Dimming:	ELV: 100-10%, 0-10V: 100-5%, TRIAC: 100-5%
Rated Life:	50,000 Hours
Standards:	ETL, cETL, Damp Location Listed
Construction	Steel frame with K9 crystal diffuser

REPLACEMENT PARTS

RPL-GLA-29308 - PD-29308 Crystal

Fixture Type: _____

Catalog Number: _____

Project: _____

Location: _____



FINISHES:



Aged Brass

Black

LINE DRAWING:

